

W 24-230 MVT (606467460) Angle Grinder
(110-120 V / AC/DC 0/50/60 Hz); Cardboard box

Order no. 606467460
EAN 4007430268198



Product may differ from Image



- Metabo Long-life motor with patented dust protection for long service life
- Metabo safety switch prevents unintentional start
- Deadman's switch for high user protection
- Tool-free adjustable guard; twist-proof
- Metabo VibraTech (MVT): integrated damping system and side handle to reduce vibrations in order to protect the user's health
- Side handle can be mounted in three positions
- Rotating main handle: high safety and better handling when cutting
- Auto-stop carbon brushes to protect the motor

Technical data

Characteristics

| | |
|------------------------------|--------------------|
| Grinding wheel Ø | 230 mm / 9 " |
| No-load speed | 6600 /min |
| Revolutions at rated load | 4600 /min |
| Torque | 17 Nm / 150 in-lbs |
| Spindle thread | 5/8" - 11 UNC |
| Weight (without power cable) | 5.8 kg / 12.8 lbs |
| Cable length | 4 m / 13 ft |

Vibration

| | |
|------------------------------|----------------------|
| Surface grinding | 4.8 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Grinding with sandpaper | 2.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|-----------|
| Sound pressure level | 94 dB(A) |
| Sound power level (LwA) | 105 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Guard
Metabo VibraTech (MVT) side handle
Flat-pin spanner
Inner support flange
Nut with two holes