

ARDEX WPM002 Liquid

Ardex (Ardex NZ)

Chemwatch: **7921-05** Version No: **2.1**

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Chemwatch Hazard Alert Code: 0

Issue Date: **06/11/2024** Print Date: **07/11/2024** L.GHS.NZL.EN.E

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

1 Today Identifier				
Product name	ARDEX WPM002 Liquid			
Chemical Name	Not Applicable			
Synonyms	Not Available			
Chemical formula	Not Applicable			
Other means of identification	Not Available			

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

The liquid component of two part Superflex waterproof coating. When mixed with the powder component in accordance with manufacturers directions, can be applied over conventional surfaces in wet areas and balconies. Will dry to form a flexible and tough waterproof membrane. Applied by brush or roller.

Use according to manufacturer's directions.

Details of the manufacturer or supplier of the safety data sheet

Registered company name	Ardex (Ardex NZ)			
Address	32 Lane Street Woolston Christchurch New Zealand			
Telephone	84 3029 +64 3384 9779			
Fax	64 3384 9779			
Website	www.ardex.co.nz			
Email	info@ardexnz.com			

Emergency telephone number

Association / Organisation	Ardex (Ardex NZ)			
Emergency telephone number(s)	+64 3 373 6900			
Other emergency telephone number(s)	0800 764 766 (NZ NPC)			

SECTION 2 Hazards identification

Classification of the substance or mixture

Considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Not regulated for transport of Dangerous Goods.

Classification [1]	Hazardous to the Aquatic Environment Long-Term Hazard Category 3				
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI				
Determined by Chemwatch using GHS/HSNO criteria	9.1C				

Label elements

Luber elements				
Hazard pictogram(s)	Not Applicable			
Signal word	Not Applicable			

Hazard statement(s)

H412 Harmful to aquatic life with long lasting effects.

Page 2 of 11 ARDEX WPM002 Liquid

Issue Date: **06/11/2024**Print Date: **07/11/2024**

Precautionary statement(s) Prevention

P273 Avoid release to the environment.

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight] Name			
330-54-1	<0.1	diuron		
10605-21-7	<0.1	carbendazim		
26530-20-1	<0.1	2-octyl-4-isothiazolin-3-one		
Not Available	balance Ingredients determined not to be hazardous			
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available			

SECTION 4 First aid measures

Description of first aid measures

besomption of mot did incustres					
Eye Contact If this product comes in contact with eyes: Wash out immediately with water. If irritation continues, seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.					
Skin Contact If skin or hair contact occurs: ► Flush skin and hair with running water (and soap if available). ► Seek medical attention in event of irritation.					
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary. 				
Ingestion Ingestion					

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.			
Advice for firefighters				
Fire Fighting	 Use water delivered as a fine spray to control fire and cool adjacent area. Do not approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use. 			
Fire/Explosion Hazard	 Non combustible. Not considered a significant fire risk, however containers may burn. 			

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- ► Control personal contact with the substance, by using protective equipment.

ARDEX WPM002 Liquid

Page 3 of 11 Issue Date: 06/11/2024 Print Date: 07/11/2024

	 Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal.
Major Spills	Minor hazard. Clear area of personnel. Alert Fire Brigade and tell them location and nature of hazard. Control personal contact with the substance, by using protective equipment as required. Prevent spillage from entering drains or water ways. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Absorb remaining product with sand, earth or vermiculite and place in appropriate containers for disposal. Wash area and prevent runoff into drains or waterways. If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling Limit all unnecessary personal contact. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Avoid contact with incompatible materials. When handling, **DO NOT** eat, drink or smoke ▶ Keep containers securely sealed when not in use Safe handling Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Use good occupational work practice. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. • Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained. Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Other information Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks.

Conditions for safe storage, including any incompatibilities

Suitable container	 Polyethylene or polypropylene container. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	None known

▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source

	•							
New Zealand Workplace Exposure Standards (WES)	diuron	Diuron	10 mg/m3	Not Available	Not Av	vailable	carcinogen category 2 - Suspected human carcinogen	
Ingredient	Original IDL	Original IDLH			R	Revised IDLH		
diuron	Not Available	Not Available			N	Not Available		
carbendazim	Not Available	Not Available			N	Not Available		
2-octvl-4-isothiazolin-3-one	Not Available	Not Available			N	Not Available		

Ingredient Material name TWA STEL

Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit			
carbendazim	E	≤ 0.01 mg/m³			
2-octyl-4-isothiazolin-3-one	E	≤ 0.1 ppm			
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.				

MATERIAL DATA

Exposure controls

Appropriate engineering	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls
controls	can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
	The basic types of engineering controls are:
	Process controls which involve changing the way a job activity or process is done to reduce the risk.
	Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that

strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.

Peak

Notes

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in

Chemwatch: **7921-05**Page **4** of **11**Issue Date: **06/11/2024**Version No: **2.1**Print Date: **07/11/2024**

ARDEX WPM002 Liquid

the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air)	0.25-0.5 m/s (50- 100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100- 200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200- 500 f/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

effectively remove the contaminant

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Individual protection measures, such as personal protective equipment









Eye and face protection

Safety glasses with side shields

Chemical goggles.
 Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]

Skin protection

See Hand protection below

▶ Wear general protective gloves, eg. light weight rubber gloves.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

- · frequency and duration of contact,
- · chemical resistance of glove material,
- · glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

- · When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- \cdot When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.
- · Contaminated gloves should be replaced.

As defined in ASTM F-739-96 in any application, gloves are rated as:

- · Excellent when breakthrough time > 480 min · Good when breakthrough time > 20 min
- · Fair when breakthrough time < 20 min
- · Poor when glove material degrades

For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
 Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion
- or puncture potential

 Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfume

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Body protection

See Other protection below

Other protection

Hands/feet protection

No special equipment needed when handling small quantities

OTHERWISE:

Overalls.

ARDEX WPM002 Liquid

Issue Date: **06/11/2024**Print Date: **07/11/2024**

- ▶ Barrier cream.
- ▶ Eyewash unit.

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index"

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

ARDEX WPM002 Liquid

Material	CPI
BUTYL	A
NEOPRENE	A
NEOPRENE/NATURAL	A
NITRILE	A
PE	A
PE/EVAL/PE	A
PVC	Α
TEFLON	A
VITON	A
NATURAL RUBBER	В
NATURAL+NEOPRENE	В

^{*} CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Ansell Glove Selection

Glove — In order of recommendation
AlphaTec® 15-554
AlphaTec® Solvex® 37-185
AlphaTec® 38-612
AlphaTec® 58-008
AlphaTec® 58-530B
AlphaTec® 58-530W
AlphaTec® 58-735
AlphaTec® 79-700
AlphaTec® Solvex® 37-675
DermaShield™ 73-711

The suggested gloves for use should be confirmed with the glove supplier.

Respiratory protection

Type BAX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	BAX-AUS P2	-	BAX-PAPR-AUS / Class 1 P2
up to 50 x ES	-	BAX-AUS / Class 1 P2	-
up to 100 x ES	-	BAX-2 P2	BAX-PAPR-2 P2 ^

^{^ -} Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties Appearance Milky white liquid with characteristic odour; mixes with water. Physical state Relative density (Water = 1) 1.04 Liauid Partition coefficient n-octanol Odour Characteristic Not Available / water Auto-ignition temperature Odour threshold Not Available Not Applicable (°C) Decomposition pH (as supplied) 8 5-9 5 Not Available temperature (°C) Melting point / freezing point Not Applicable Viscosity (cSt) Not Available Initial boiling point and ~100 Molecular weight (g/mol) Not Applicable boiling range (°C) Flash point (°C) Not Applicable Taste Not Available **Evaporation rate** Not Available **Explosive properties** Not Available Flammability Not Applicable **Oxidising properties** Not Available Surface Tension (dyn/cm or Upper Explosive Limit (%) Not Applicable Not Available Lower Explosive Limit (%) Not Applicable Volatile Component (%vol) 45-47

Page 6 of 11

ARDEX WPM002 Liquid

Issue Date: 06/11/2024 Print Date: 07/11/2024

Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
Heat of Combustion (kJ/g)	Not Available	Ignition Distance (cm)	Not Available
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7	
Chemical stability	roduct is considered stable and hazardous polymerisation will not occur.	
Possibility of hazardous reactions	See section 7	
Conditions to avoid	See section 7	
Incompatible materials	See section 7	
Hazardous decomposition products	See section 5	

SECTION 11 Toxicological information

Information of	n toxicolo	gical effects
----------------	------------	---------------

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.
Еуе	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course. Chronic effects of exposure to diuron may initially include skin irritation, or blurring of vision, liver enlargement; spleen and thyroid effects; red blood cell destruction; or reduction of the blood's oxygen carrying capacity with cyanosis (bluish discolourisation), weakness or shortness of breath by formation of methemoglobin. Significant skin permeation after contact appears unlikely. There are no reports of human sensitisation to diuron. At 2500 ppm diuron in the diet for 2 years, rats and dogs showed growth retardation, slight anaemia, presence of abnormal pigmentation, increased anythropiesis and splenic harmonidancies.

increased erythropolesis and spienic naemosiderosis.		
ADDEVMONOST	TOXICITY	IRRITATION
ARDEX WPM002 Liquid	Not Available	Not Available
	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]
diuron	Inhalation (Rat) LC50: >5.05 mg/l4h ^[1]	Skin: no adverse effect observed (not irritating) ^[1]
	Oral (Rat) LD50: 1017 mg/kg ^[2]	
carbendazim	TOXICITY	IRRITATION
	dermal (rat) LD50: 2000 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]
	Oral (Dog) LD50; >2500 mg/kg ^[2]	Skin: no adverse effect observed (not irritating) ^[1]
	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 311 mg/kg ^[2]	Eye (Rodent - rabbit): 100mg - Severe
2-octyl-4-isothiazolin-3-one	Oral (Rat) LD50: 248 mg/kg ^[2]	Eye: adverse effect observed (irreversible damage) ^[1]
		Skin (Human): 0.1%
		Skin (Rodent - rabbit): 500mg/24H
		Skin: adverse effect observed (corrosive) ^[1]
		Skin: adverse effect observed (irritating) ^[1]

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

DIURON

Note: Equivocal animal tumorigenic agent by RTECS criteria. NOTE: This substance may contain impurities (tetrachlorazobenzene and tetrachloroazoxybenzene). Maximum impurity levels are proscribed under various jurisdictions ADI: 0.006 mg/kg/day NOEL: 0.625 mg/kg/day No significant acute toxicological data identified in literature search.

Chemwatch: **7921-05**Page **7** of **11**Issue Date: **06/11/2024**Version No: **2.1**Print Date: **07/11/2024**

ARDEX WPM002 Liquid

Diuron is absorbed readily through the gut and lungs while uptake through the skin is more limited. It is slightly toxic to mammals but juveniles are more susceptible than adults(18). The oral LD50 in rats is 3-4 g/kg and the dermal LD50 is > 2 g/kg(19). An early study indicated that animals fed protein-deficient diets were considerably more vulnerable to diuron toxicity; rats fed a diet of 3% protein were five times more sensitive to diuron.

Exposure to sub-lethal doses of diuron causes formation of methaemoglobin, an abnormal form of the protein haemoglobin which carries oxygen in the blood. Diuron can decrease the number of red blood cells (RBCs), increase the number of abnormally shaped RBCs, and increase the number of white blood cells. Diuron may cause the spleen to become congested due to the increased demand to remove damaged RBCs. Increases in liver size are also observed and are indicative of the extra load placed on this organ, the body s major site of detoxification. Diuron can also cause eye and skin irritation.

Diuron contains two significant impurities from the manufacturing process 3,3',4,4'-tetrachloroazobenzene (TCAB) and 3,3',4,4'-tetrachloroazoxybenzene (TCAOB), both potent 'dioxin-like substances. TCAB levels between 0.15 and 28 ppm have been found in diuron samples tested. TCAOB is present at lower levels. Both TCAB and TCAOB cause chloracne a serious skin disease

Carcinogenicity: The US Environmental Protection Agency (EPA) has classified diuron as a 'known/likely' carcinogen since 1997 based on the results of two studies. One study on rats indicated that both males and females fed diuron had a higher incidence of bladder cancer than control animals. The male rats in this study also had a higher incidence of kidney cancer than the control animals. In a study of mice animals with higher exposures had more breast cancer

Mutagenicity: There is conflicting evidence on whether diuron can cause mutations

Developmental Toxicity: Rats fed relatively high levels (125 mg/kg/day) of diuron produced offspring with delayed bone formation(26) and other studies indicate that similar levels of diuron reduce birth weight. The US Toxics Release Inventory list diuron as a developmental toxin In mammals, metabolism principally occurs through hydroxylation and dealkylation.

Metabolites. Breakdown of this compound is similar in animals, plants and soil. The first step is N-demethylation followed by ring cleavage. The main breakdown product of diuron is 3,4-dichloroaniline (3,4-DCA). The oral LD50 of 3,4-DCA in rats is around 60 mg/kg and by the inhalation route the LC50 ranges from 2.8 to 4.7 mg/l/4hrs indicating that 3,4-DCA is considerably more toxic than diuron itself. Dermal and inhalation absorption is rapid leading to formation of methaemoglobin. A marked species difference is dermal toxicity is noted with rabbit considerably more sensitive than rats. No human data is available but by extrapolating from other aromatic amines humans could be considerably more sensitive to methaemoglobin formation than rats. 3,4-DCA should be regarded as a potential respiratory sensitiser. The carcinogenic potential of 3,4-DCA remains uncertain.

Intraperitoneal (Rat, adult male) LD50: 7320 mg/kg * Intraperitoneal (Rat, adult female) LD50: 15000 mg/kg * Inhalation LC50 (4 h) for rats, rabbits, guinea pigs or cats no effect with suspension (10 g/l water). * NOEL (2 y) for dogs 300 mg/kg diet, corresponding to 6-7 mg/kg b.w. ADI 0.01 mg/kg b.w. * Toxicity Class WHO III;EPA IV

Exposure to the material may result in a possible risk of irreversible effects. The material may produce mutagenic effects in man. This concern is raised, generally, on the basis of

appropriate studies using mammalian somatic cells in vivo. Such findings are often supported by positive results from in vitro mutagenicity studies.

for carbendazim:

Benomyl (a precursor to carbendazim) causes dermal sensitization in humans. Benomyl and carbendazim represent a very low risk for acute poisoning in humans.

In animal systems, carbendazim is metabolized to (5-hydroxy- 1H-benzimidazol-2-yl)-carbamate (5-HBC) and other polar metabolites, which are rapidly excreted. Carbendazim has not been observed to accumulate in any biological system.

Carbendazim has low acute toxicity. The LD50 values range from > 2000 to 15 000 mg/kg in a wide variety of test animals and routes of administration. However, significant adverse reproductive effects have been noted following a single exposure

Carbendazim is well absorbed (80-85%) after oral exposure but much less so by dermal exposure. Absorbed carbendazim is metabolised into many compounds within the organism. The main metabolites are 5-HBC and 5,6-HOBC-N-oxides. The tissue distribution of carbendazim showed no bioconcentration. In the rat, the highest concentration after oral carbendazim administration (< 1% of the dose) occurred in the liver. It was distributed as carbendazim in the mitochondria, 5-HBC in the cytostol, and 2-aminobenzimidazole (2-AB) in the microsomes. Carbendazim is excreted in the urine and faeces within 72 h after oral dosing in rats. In rats and mice, high doses of carbendazim, both in the diet and by gavage, affect certain liver microsomal enzymes.

Short-term exposure Dietary administration of carbendazim for up to 90 days produced slight effects on liver weight in female rats exposed to 360 mg/kg body weight per day. In a 90-day gavage study in the rat, the NOEL was 16 mg/kg per day based on hepatotoxicity. Short-term feeding studies on dogs were not adequate for establishing a NOEL. A 10-day dermal study in the rabbit revealed no systemic toxicity at the only dose tested (200 mg/kg).

Long-term exposure Male and female rats fed 2500 mg/kg diet showed reduced erythrocyte count and haemoglobin and haematocrit values. No liver-related toxicity was noted. Male rats fed 2500 mg/kg diet or more presented a marginal increase in diffuse testicular atrophy and prostatitis. The NOEL in the rat is 500 mg/kg diet.

Male and female mice fed 5000 mg/kg diet showed increased absolute liver weight. There was also significant centrilobular hypertrophy, necrosis and swelling of the liver in male mice fed 1500 mg/kg diet.

Reproduction, embryotoxicity and teratogenicity Carbendazim was without adverse effects on reproduction when it was fed to rats in a three-generation reproduction study at levels up to and including 500 mg/kg diet. Male fertility was depressed in rats when carbendazim (200 mg/kg per day) was administered by gavage for 85 days. A dose of 50 mg/kg body weight per day in this study caused a significant decrease in epididymal sperm count.

Following a single oral dose to rats, histological examination revealed early (0-2 days) disruption of spermatogenesis with occlusion of efferent ducts and increased testicular weights at 100 mg/kg body weight. No effect was observed at 50 mg/kg in this single dose study. These effects persisted until day 70 in rats treated with 400 mg/kg.

Carbendazim caused an increase in malformations and anomalies in rats when administered at daily dose levels greater than 10 mg/kg on days 7-16 of gestation. There was a slightly decreased rate of implantation in rabbits administered 20 and 125 mg/kg per day on days 7-19 of gestation and an increased incidence of resorption at 125 mg/kg per day. Maternal toxicity was observed at 20 mg/kg per day and 125 mg/kg per day in the rat and rabbit, respectively.

In rats there was a significant increase in foetal malformations at 90 mg/kg per day. These consisted primarily of hydrocephaly, microphthalmia, anophthalmia, malformed scapulea and axial skeletal malformations (vertebral, rib and sternebral fusions, exencephaly, hemivertebrae and rib hyperplasia). However, in the rabbit there were no significant malformations.

Mutagenicity and related end-points Assays in mammalian and non-mammalian systems *in vitro* and *in vivo* and in somatic cells as well as in germ cells show that carbendazim does not interact with DNA, induce point mutation or cause germ cell mutation. Carbendazim does, however, cause numerical chromosome aberrations (aneuploidy and/or polyploidy) in experimental systems, both *in vitro* and *in vivo*.

Carcinogenicity: Benomyl and its decomposition product carbendazim feeding resulted in an increase in the incidence of hepatocellular tumours in CD-1 and SPF Swiss mice. A carcinogenicity study of carbendazim using CD-1 mice showed a statistically significant doserelated increase in the incidence of hepatocellular neoplasia in females. There was also a statistically significant increase in the mid-dose (1500 mg/kg diet) males, but not in the high-dose males because of a high mortality rate. A carcinogenicity study of carbendazim in a genetically related mouse strain, SPF mice (Swiss random strain) at doses of 0, 150, 300 and 1000 mg/kg diet (increased to 5000 mg/kg during the study) showed an increase in the incidence of combined hepatocellular adenomas and carcinomas. Carcinogenicity studies of both benomyl and carbendazim in rats were negative.

Mechanism of toxicity - mode of action The biological effects of benomyl and carbendazim result from their interaction with cell microtubules. These structures are involved in vital functions such as cell division, which is inhibited by benomyl and carbendazim. Benomyl and carbendazim toxicities in mammals are linked to microtubular dysfunction. Benomyl and carbendazim, as well as other benzimidazole compounds, display species-selective toxicity. This selectivity is, at least in part, explained by the different binding of benomyl and carbendazim to tubulins of target and non-target species

[* The Pesticides Manual, Incorporating The Agrochemicals Handbook, 10th Edition, Editor Clive Tomlin, 1994, British Crop Protection Council]

2-OCTYL-4-ISOTHIAZOLIN-3-

.IN-3- ROHM & HAAS Data ADI: 0.03 mg/kg/day NOEL: 60 mg/kg/day

The following information refers to contact allergens as a group and may not be specific to this product.

Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance

Continued...

CARBENDAZIM

ARDEX WPM002 Liquid

Page 8 of 11 Issue Date: 06/11/2024 Print Date: 07/11/2024

which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons

Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.

Acute Toxicity	X Carcinogenicity	×
Skin Irritation/Corrosion	X Reproductivity	×
Serious Eye Damage/Irritation	X STOT - Single Exposure	×
Respiratory or Skin sensitisation	X STOT - Repeated Exposure	×
Mutagenicity	X Aspiration Hazard	×

Data either not available or does not fill the criteria for classification

— Data available to make classification

SECTION 12 Ecological information

Toxicity

	Endpoint	Test Duration (hr)	Species	Value	Source
ARDEX WPM002 Liquid	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	96h	Algae or other aquatic plants	0.001mg/l	4
	BCF	1008h	Fish	<2.9-14	7
diuron	EC50	72h	Algae or other aquatic plants	0.001mg/L	4
	EC10(ECx)	1h	Algae or other aquatic plants	<0.001mg/L	4
	EC50	48h	Crustacea	>0.677mg/L	4
	LC50	96h	Fish	0.5mg/L	4
	Endpoint	Test Duration (hr)	Species	Value	Sourc
	EC50	96h	Algae or other aquatic plants	19.056mg/l	4
	BCF	1008h	Fish	0.6-1.1	7
carbendazim	EC50	72h	Algae or other aquatic plants	1.3mg/l	2
Garbenadzini	NOEC(ECx)	96h	Fish	0.001mg/L	4
	EC50	48h	Crustacea	0.02mg/L	4
	LC50	96h	Fish	0.006- 0.009mg/L	4
	Endpoint	Test Duration (hr)	Species	Value	Sourc
	EC50	96h	Algae or other aquatic plants	0.15mg/l	2
	NOEC(ECx)	840h	Fish	0.009mg/L	4
-octyl-4-isothiazolin-3-one	EC50	48h	Crustacea	0.057- 0.178mg/L	4
	LC50	96h	Fish	0.041- 0.104mg/l	4

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. DO NOT discharge into sewer or waterways

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
diuron	HIGH	HIGH
carbendazim	HIGH	HIGH
2-octyl-4-isothiazolin-3-one	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation	
diuron	LOW (BCF = 14)	
carbendazim	LOW (BCF = 3.5)	
2-octyl-4-isothiazolin-3-one	LOW (LogKOW = 2.561)	

Page **9** of **11**

Issue Date: **06/11/2024**Print Date: **07/11/2024**

ARDEX WPM002 Liquid

Mobility in soil

Ingredient	Mobility
diuron	LOW (Log KOC = 136)
carbendazim	LOW (Log KOC = 175.8)
2-octyl-4-isothiazolin-3-one	LOW (Log KOC = 2120)

SECTION 13 Disposal considerations

Waste treatment methods

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Product / Packaging disposal
- Recycle wherever possible.
 Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or incineration in a licensed apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

Do not dispose to the environment any component, which may be biocumulative or not rapidly degradable.

Only discharge the substance to the environment if an environmental exposure limit has been set for the substance.

Only deposit the hazardous substance into or onto a landfill or sewage facility or incinerator, where the hazardous substance can be handled and treated appropriately.

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO	
HAZCHEM	Not Applicable	

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
diuron	Not Available
carbendazim	Not Available
2-octyl-4-isothiazolin-3-one	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
diuron	Not Available
carbendazim	Not Available
2-octyl-4-isothiazolin-3-one	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard	
HSR002544	Construction Products Subsidiary Hazard Group Standard 2020	

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

diuron is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

New Zealand Approved Hazardous Substances with controls

ARDEX WPM002 Liquid

Page 10 of 11 Issue Date: 06/11/2024

Print Date: 07/11/2024

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Land Transport Rule: Dangerous Goods 2005 - Schedule 1 Quantity limits for dangerous goods

New Zealand Workplace Exposure Standards (WES)

carbendazim is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Land Transport Rule: Dangerous Goods 2005 - Schedule 1 Quantity limits for dangerous goods

2-octyl-4-isothiazolin-3-one is found on the following regulatory lists

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

Additional Regulatory Information

Not Applicable

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantities
Not Applicable	Not Applicable

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable

Tracking Requirements

Not Applicable

National Inventory Status

Mational inventory otatas	
National Inventory	Status
Australia - AIIC / Australia Non- Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (diuron; carbendazim; 2-octyl-4-isothiazolin-3-one)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	06/11/2024
Initial Date	06/11/2024

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

ARDEX WPM002 Liquid

Issue Date: 06/11/2024 Print Date: 07/11/2024

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be

Definitions and abbreviations

- ▶ PC TWA: Permissible Concentration-Time Weighted Average
- ▶ PC STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- ► TEEL: Temporary Emergency Exposure Limit。
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ▶ ES: Exposure Standard
- ▶ OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
 LOAEL: Lowest Observed Adverse Effect Level
- ▶ TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- BEI: Biological Exposure IndexDNEL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration
- ▶ AllC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ENCS: Existing and New Chemical Substances Inventory
 KECI: Korea Existing Chemicals Inventory
 NZIoC: New Zealand Inventory of Chemicals

- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ▶ TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.