

Bona Polish Remover

Technical data sheet

Bona Polish Remover is used to remove build up from polish and other maintenance coatings. Suitable for water resistant floorings such as varnished wooden floors, tiles, PVC.

- Effective and easy to use
- Waterbased
- Non-offending odour

Technical data

| | |
|--------------------|---|
| pH-value: | Approx. 11,5 |
| Coverage: | Approx. 70 m ² /litre |
| Shelf life: | 3 years from date of production in unopened original container |
| Storage/transport: | The temperature must not fall below +5°C or exceed +25°C during storage and transport. |
| Safety: | Causes serious eye damage. Causes skin irritation. Hazardous ingredients : Isotridecanol, ethoxylated 2-aminoethanol |
| Disposal: | Wastes and emptied containers should be handled in accordance with local regulations. |
| Sizes: | 1L |

Preparations

Remove loose dirt and grit from your floor. Ensure floor is in sound condition and that the floor seal is intact. Do not allow Polish Remover into open gaps in the floor, may cause permanent stain.

Dilute 1 litre concentrate with 5 litres of clean water in a bucket. Prepare a second bucket with only clean water.

Instructions for use

1. Apply Bona Polish Remover solution on a small section of the floor and let it dissolve the polish for approx. 5 minutes.
2. Scrub the wetted section with a hard bristled brush or a scouring pad.
3. Wipe off the dissolved material with a mop from the bucket with clean water.
4. Continue working section by section until the whole floor has been treated. Replace the cleaning water frequently.
5. Once the polish has been removed, rinse the surface one more time using clean water.

Note: Use water restrictively on wooden floors. All traces of Bona Polish Remover must be removed before applying new coats of Polish or Refresher.

For more information visit bona.com

