

Bona Decking Oil

Technical data sheet

Bona Decking Oil is a concentrated blend of vegetable oils, modified for superior impregnation and long-lasting protection of wooden decking and other exterior wood surfaces. It enhances the natural wood grain while protecting against moisture ingress and reducing the potential of wood cracking and warping.

- Long lasting protection against the weather elements
- Contains UV protection
- Reduces wood cracking and warping
- Rapid drying and easy to apply
- Low VOC content and low odour

Technical data

Type of oil:	Modified vegetable oil
Colours:	Neutral, Mahogany, Teak, Grey
VOC:	~6%
Dilution:	Do not dilute
Drying time:	- Between applications: 30-60 minutes* - Light use: 24 hours*
Application tools:	Brush, roller or other suitable applicator
Total consumption:	Approx. 20 m ² /litre, depending on wood type and application.
Safety:	Unclassified
Fire risk:	Non-flammable. Risk of self-ignition, see safety data sheet for more information.
Cleaning:	Clean tools with white spirit. Dried material can be removed with white spirit.
Shelf life:	2 years from the date of production in unopened original container.
Storage/transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport.
Disposal:	Wastes and emptied containers should be handled in accordance with local regulations
Pack size:	2 x 2,5 litres 1 x 10 litres (only neutral)

Preparations

The surface which is to be treated must consist of bare wood and be dry. Moisture content of the wood should not exceed 18% RH. Oiled, waxed and/or decayed wood should be thoroughly cleaned with Bona Deep Clean System or Bona Decking Reviver prior to applying new oil.

New installed wood decking must not be treated immediately after installation but must first be exposed to several weeks of weathering. This makes the wood porous and absorbent for the Bona Decking Oil.


Optimal application conditions are between 18-25C. High temperatures and low humidity shortens the drying time, low temperatures and high humidity prolong the drying time. Minimum temperature for use is 13C.

Application

Stir the can well.

1. Apply 1-2 coats of the oil evenly and thinly using a wide brush or other suitable applicator.
2. When the decking is saturated, wipe off all surplus oil with a cotton cloth.

Finishing



Bona[®]

Bona Decking Oil

Technical data sheet

Finishing



3. Allow at least 24 hours drying time before taking the decking into use. Avoid foot traffic during this time. If it rains on the decking before the oil has hardened, it may be necessary to re-apply a thin layer of oil.

WARNING: BONA DECKING OIL CONTAINS DRYING OILS. RISK OF SELF-IGNITION. USED CLOTHS, RAGS AND SIMILAR SHOULD BE PLACED IN WATER OR SEALED METAL CONTAINERS.

Drying time (at 20 C/60% RH): 24 h, expect longer drying time at low temperatures and high humidity.

Maintenance

Rinse decking on occasion with soap and water. If it starts to show signs of wear i.e. a lighter, dryer appearance then it is possible to apply an additional layer of Bona Decking Oil to improve the surface and extend the life length before the wear goes too far. Grey, decayed wood should be thoroughly cleansed with Bona Deep Clean System or Bona Decking Reviver prior to re-oiling.

Detailed instructions are available at www.bona.com

The information provided is prepared to the best of our current knowledge and makes no claim to be complete. User is responsible for establishing that the product and recommendations herein are fit for the designated purpose, wood type and present situation before use. Bona can only guarantee the delivered product. A professional and thereby successful application of the product is beyond our control. If in doubt make a preliminary test. User is required to read and understand all information contained on package labels and safety data sheets before using this product.