

Bona PU Filler

2-PART POLYURETHANE FILLER AND ADHESIVE





COATINGS



PREPARATION

Clean the joint, crack or hole to be filled. Cut off loose parts of mat and scrape and abrade with a suitable abrasive to clean the joint/hole. Finally wipe the joint/hole with ethanol or similar solvent and allow to dry.

It is recommended to test the product's suitability for the intended application and purpose prior to use. Given the variety of materials, substrates, site and processing conditions, no guarantee for functionality can be given.





1 | Starting point

2 | Abrade and scrape





3 | Clean and cut off edges 4 | Wipe with ethanol

APPLICATION

Open the cartridge and insert into a caulking gun. Press out material until it starts to flow. Attach mixer tip. Dispense 25-50 mm of material and discard. Fill hole/crack. For best results, make a slight "overfill".

NOTE: When not filling, keep material flowing from the cartridge with short intervals so that the material does not harden in the tip.

Bona PU Filler

2-part polyurethane filler and adhesive

2-part polyurethane filler and adhesive. Developed for guick and durable repair of resilient floorings such as PVC/LVT, Rubber and Linoleum, with great adhesion to many materials. Can also be used to glue down smaller pieces of mat. Resistant to high impact, elevated temperature, moisture as well as many solvents and chemicals.

KEY BENEFITS

- · Super quick hardening
- Excellent adhesion properties
- High durability
- Virtually odourless

APPLICATION (CONTINUED)

Leave mixer in place when finished filling. Substitute mixer when using again. Sand the repaired area with a grit 120 abrasive until the filling is flat to the surface. Coat the entire area with Bona LinoPrime or Bona Pure Colour according to separate instruction.







1 | Fill the hole/crack

2 | Smooth

3 | Sand





4 | Clean and let it dry

5 | Coat

TECHNICAL DATA

Type of coating: Polyol mixture combined with isocyanate prepolymer

Color: Light Grev Open Time: 3,5 min

Drying time: 30 min (20°C/60% R.H)

Application tools: Caulking gun

Safety: Classified, see safety data sheet for more details

Cleaning of tools: Bona Cleaning Wipes, Bona S100, acetone, ethanol.

Hardened filler can only be removed mechanically.

Pack size: 12 x 250 ml cartridges incl. 1 mixer tip per cartridge

