



Bona **LinoPrime**

FAST DRYING PUR-BASED PRIMER



Bona LinoPrime

Fast drying PUR-based primer

Bona LinoPrime is a fast drying PUR-based primer developed for linoleum floors. This unique primer delivers excellent fill, reducing absorbency in the pores of deep cleaned and sanded linoleum floors to improve levelling and smoothness in preparation for a second coat. Thanks to its fast-drying formula, overcoating may be performed in as little as one hour.

KEY BENEFITS

- Specially developed for linoleum floors
- Excellent fill reduces absorbency
- Ultra-quick drying
- Excellent levelling
- Low consumption per sqm

TECHNICAL DATA

Type of coating:	2-component waterborne polyurethane primer
Solids content:	Approx. 23%
Sheen (at 60°):	Approx. 20% (measured on glass)
VOC:	<1% VOC
Mixing ratio:	1 part Bona Pure Hardener to 19 parts Bona LinoPrime
Pot life:	Max. 3 hours at 20°C (shorter if warmer)
Dilution:	Do not dilute
Drying time:	Approx. 1-2 hours at 20°C/60% R.H.

TECHNICAL DATA (CONTINUED)

Application tools:	Bona Microfiber Roller (5mm pile)
Application rate:	20-25 m ² /litre (40-50g/m ²) per coat
Safety:	Coating: Unclassified Hardener: Classified (see Safety Data Sheet)
Shelf life:	1 year from the date of production, in unopened original container
Storage/Transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport.
Disposal:	Wastes and emptied containers should be handled in accordance with local regulations
Pack size:	3x5 litres incl. hardener (36 boxes per pallet)
Certifications:	EMICODE; class EC1RPLUS – Very low indoor emissions EN 71-3: Application on children's toys

Bona LinoPrime should never be used as the final treatment for resilient floor coverings.