



# Bona Hard-Surface Floor Polish

Protective coating for sealed hard-surface floors

Revive scratched and dull hard-surface floors and protect against wear



Apply with the  
Bona Microfiber  
Applicator Pad



**Bona Hard-Surface Floor Polish** restores the shine, while offering protection against wear. The durable, urethane acrylic blend adds a high-gloss protective layer, and fills in micro scratches, evening out the appearance of your floor for a refreshed new look. Use every 1-4 months, depending on traffic, to keep sealed hard-surface floors looking new.

- High gloss formula
- Adds a protective layer
- Fills in micro-scratches
- GREENGUARD certified

## TECHNICAL DATA

Binding agent:	Acrylic /polyurethane
Gloss:	High Gloss
Dilution:	Do not dilute
Drying time:	- Touch dry: 30-60 minutes - Recoatable: minimum 2 hours
Application tools:	Bona Microfiber Applicator Pad
Coverage:	Approx. 50 m <sup>2</sup> /litre
Safety:	The product is not classified according to European Regulation (EC) 1272/2008 and its amendments.
Cleaning:	Clean tools with detergent and warm water directly after use.
Shelf life:	2 years from date of production in unopened original container
Storage/transport:	The temperature must not fall below +5°C or exceed +30°C during storage and transport.
Disposal:	Waste and emptied containers should be handled in accordance with local regulations.
Sizes:	1L
Certification:	GREENGUARD

2024-04-08  
This data sheet replaces all previous versions  
please check [bona.com](https://bona.com) to ensure that you have  
the latest version.



# Bona Hard-Surface Floor Polish

Protective coating for sealed hard-surface floors

**Revive scratched and dull hard-surface floors and protect against wear**

## PREPARATION

Remove loose dirt and grit from your floor. Clean floor thoroughly with Bona Hard-Surface Floor Cleaner or Bona OxyPower Hard-Surface Floor Deep Cleaner (sold only in selected markets) and let dry.

Do not use over any floor that has been waxed or oiled. Wax and oil residues will prevent proper adhesion of Bona Hard-Surface Polish to the floor. **Always test a small area for desired results before use.**

## INSTRUCTIONS FOR USE

Shake bottle thoroughly before use and apply at normal room temperature, 18-25°C.

1. Pour a wide line of Bona Hard-Surface Floor Polish on a small section of the floor.
2. Spread the product over the section using a Bona Microfiber Applicator Pad.
3. Complete section by smoothing with the applicator pad, always finishing in the same direction.
4. Continue section by section until the entire floor has been treated.
5. Rinse and wash applicator pad with detergent and warm water immediately after use.

The floor can be walked on after 2 hours but avoid heavy traffic and replacement of furniture and rugs until after the first 12 hours.

## MAINTENANCE

Regularly clean your floors with Bona Wood Hard-Surface Cleaner and a Bona Microfiber Cleaning Pad. When the floor is starting to show signs of wear and needs freshening up, clean and apply a new coat of Bona Hard-Surface Floor Polish. For periodic removal of polish build up use Bona Polish Remover.

**For more information, please visit [bona.com](https://bona.com)**