

# **Bona Retarder**

## Additive to slow drying & curing.



Bona Retarder improves levelling and extends the open time of Bona waterborne lacquers. It is compatible with primers and topcoats from both the wood and the resilient range of coatings from Bona<sup>1</sup>. It is designed to be used when the indoor humidity is low and/or the temperature of the room is higher than normal. Bona Retarder facilitates the application and reduces the risk of application marks and bubbles which may occur because of a rapid drying process.

- Facilitates application in dry and/or warm climatic conditions
- Prolongs open time
- Reduces the risk of overlapping and discolouration

### **TECHNICAL DATA**

Mixing ratio: Lacguers & primers: max 4%

Safety: Unclassified.
Flash point: Non-flammable.

Shelf life: Two years from the date of production, in unopened original container.

Disposal: Waste and emptied containers should be handled in accordance with local

regulations.

Storage/transport: The temperature must not fall below +5°C or exceed +30°C during storage or

transportation.

Pack size: 12 x 200 ml (120 boxes per pallet).

Additional detailed information is noted in the appropriate Safety Data Sheet.



check bona.com to ensure you have the latest version



# **Bona Retarder**

## Additive to slow drying & curing.

#### **IMPORTANT**

When using retarder with two component products, retarder must be added only **after** finish and hardener have been thoroughly mixed.

#### **DIRECTIONS FOR USE**

**Bona Waterborne Lacquer** 

Add maximum 4% Bona Retarder to the lacquer and shake or stir in thoroughly.

Apply lacquer mixed with Bona Retarder as normal according to the instructions on each product's technical data sheet.

<sup>1</sup> Note: Bona Retarder is not recommended for use with Bona Mega Natural.

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and extensive testing but makes no claim to be complete. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice from Bona before use. Bona can only guarantee its products and not the construction as a whole. Observe recommendations from flooring manufacturer and the provisions of relevant standards.

