



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Hazardous Substances (Safety Data Sheets) Notice 2017 EPA Consolidation 30
September 2022

BOSTIK SILICONE INDUSTRIAL GRADE CLEAR
Revision Number 2

Revision date 14-Mar-2025
Supersedes date 25-Oct-2021

Section 1: Identification

Product identifier

Product Name BOSTIK SILICONE INDUSTRIAL GRADE CLEAR

Other means of identification

Recommended use of the chemical and restrictions on use

Recommended use Sealant

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier

Bostik New Zealand Limited
19 Eastern Hutt Road Wingate,
Lower Hutt, New Zealand
Tel: 04-567 5119
Fax: 04-567 5412

Manufacturer

Bostik New Zealand Limited
19 Eastern Hutt Road Wingate,
Lower Hutt, New Zealand
Tel: 04-567 5119
Fax: 04-567 5412

E-mail address SDS.AP@Bostik.com

Emergency telephone number

Emergency Telephone 24 Hr: 0800 243 622
International +64 4 917 9888
Poison Centre : 0800 764 766

Section 2: Hazard identification

GHS Classification

Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 2

Label elements



Signal word
Danger

Hazard statements

H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage

SAFETY DATA SHEET

BOSTIK SILICONE INDUSTRIAL GRADE CLEAR
Revision Number 2

Revision date 14-Mar-2025
Supersedes date 25-Oct-2021

H351 - Suspected of causing cancer
H371 - May cause damage to organs

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Contaminated work clothing should not be allowed out of the workplace
Do not breathe dust
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Wear protective gloves

Precautionary Statements - Response

IF exposed or concerned: Call a POISON CENTER or doctor

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Immediately call a POISON CENTER or doctor

Skin

IF ON SKIN: Wash with plenty of water and soap
If skin irritation or rash occurs: Get medical advice/attention
Take off contaminated clothing and wash it before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable

Other hazards which do not result in classification

Small amounts of 2-butanone, oxime (CAS 96-29-7) are formed by hydrolysis and released upon curing. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. May be harmful if swallowed. Causes mild skin irritation.

Section 3: Composition/information on ingredients

Chemical name	CAS No.	Weight-%
2-Butanone, O,O',O''-(methylsilyldiyl)trioxime	22984-54-9	5 - <10
Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime	2224-33-1	1 - <5
N-(3-(trimethoxysilyl)propyl)ethylenediamine	1760-24-3	1 - <3
2-Butanone, oxime	96-29-7	1 - <3
Dibutyltin dilaurate	77-58-7	0.1- <1

Non-hazardous ingredients	Proprietary	Balance
---------------------------	-------------	---------

Section 4: First-aid measures

Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.
Inhalation	Remove to fresh air. If symptoms persist, call a physician.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.
Skin contact	Wash off immediately with soap and plenty of water for at least 15 minutes. May cause an allergic skin reaction. If symptoms persist, call a physician.

SAFETY DATA SHEET

BOSTIK SILICONE INDUSTRIAL GRADE CLEAR
Revision Number 2

Revision date 14-Mar-2025
Supersedes date 25-Oct-2021

Ingestion	Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.
Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).
<u>Most important symptoms and effects, both acute and delayed</u>	
Symptoms	None known.
Effects of Exposure	May cause damage to organs.
<u>Indication of any immediate medical attention and special treatment needed</u>	
Note to physicians	Treat symptomatically.

Section 5: Fire-fighting measures

Suitable Extinguishing Media

Suitable Extinguishing Media	Water spray, carbon dioxide (CO ₂), dry chemical, alcohol-resistant foam.
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	Full water jet.

Specific hazards arising from the chemical

Specific hazards arising from the chemical	Thermal decomposition can lead to release of irritating gases and vapors.
Hazardous combustion products	Carbon dioxide (CO ₂). Nitrogen oxides (NO _x). Silicon oxides.

Special protective actions for fire-fighters

Special protective equipment and precautions for fire-fighters	Wear self contained breathing apparatus for fire fighting if necessary.
----------------------------------------------------------------	-------------------------------------------------------------------------

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation.
Other information	Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions	Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.
---------------------------	--------------------------------------------------------------------------------------------------------------------------------------

Methods and material for containment and cleaning up

Methods for containment	Do not scatter spilled material with high pressure water streams.
Methods for cleaning up	Pick up and transfer to properly labeled containers.

SAFETY DATA SHEET

BOSTIK SILICONE INDUSTRIAL GRADE CLEAR
Revision Number 2

Revision date 14-Mar-2025
Supersedes date 25-Oct-2021

Precautions to prevent secondary hazards

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: Handling and storage

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Take off contaminated clothing and wash before reuse.

General hygiene considerations Take off contaminated clothing and wash it before reuse.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Keep away from food, drink and animal feeding stuffs. Protect from moisture.

Recommended storage temperature Keep at temperatures between 50 and 95 °F / 10 and 35 °C.

Incompatible materials Strong oxidizing agents.

Section 8: Exposure controls/personal protection

Working area parameters, subject to mandatory control (MAC or TSEL)

Exposure Limits Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

Chemical name	New Zealand	ACGIH TLV	United Kingdom	Australia
Dibutyltin dilaurate 77-58-7	TWA: 0.05 mg/m ³ STEL: 0.02 mg/m ³ STEL: 0.1 mg/m ³ Sk*	TWA: 0.1 mg/m ³ Sn STEL: 0.2 mg/m ³ Sn Sk*	TWA: 0.1 mg/m ³ ; STEL: 0.2 mg/m ³ ; pSk	TWA: 0.1 mg/m ³ ; STEL: 0.2 mg/m ³ ;
Chemical name	New Zealand	ACGIH TLV	United Kingdom	Australia
Methyl alcohol 67-56-1	TWA: 200 ppm TWA: 262 mg/m ³ STEL: 250 ppm STEL: 328 mg/m ³ Sk*	TWA: 200 ppm STEL: 250 ppm Sk*	TWA: 200 ppm; TWA: 266 mg/m ³ ; STEL: 250 ppm; STEL: 333 mg/m ³ ; pSk	TWA: 200 ppm; TWA: 262 mg/m ³ ; STEL: 250 ppm; STEL: 328 mg/m ³ ;

Biological occupational exposure limits This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies.

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

SAFETY DATA SHEET

BOSTIK SILICONE INDUSTRIAL GRADE CLEAR
Revision Number 2

Revision date 14-Mar-2025
Supersedes date 25-Oct-2021

Hand protection	Wear suitable gloves.
Skin and body protection	Wear suitable protective clothing.
Respiratory protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
Environmental exposure controls	No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state	Paste / Gel Liquid
Appearance	Paste
Color	Clear, colorless
Odor	Characteristic.
Odor threshold	No information available

Property	Values	Remarks • Method
pH	No data available	Not applicable Insoluble in water
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	None known
Flash point	No data available	None known
Evaporation rate	No data available	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	None known
Relative vapor density	No data available	None known
Relative density	No data available	None known
Water solubility	Insoluble in water	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	
Explosive properties	No information available.	
Oxidizing properties	No information available.	

Other information

Softening point	No information available
Molecular weight	No information available
VOC content	No information available
Density	1 g/cm ³
Bulk density	No information available
Particle characteristics	

Section 10: Stability and reactivity

Reactivity

Reactivity	Product cures with moisture.
------------	------------------------------

SAFETY DATA SHEET

BOSTIK SILICONE INDUSTRIAL GRADE CLEAR
Revision Number 2

Revision date 14-Mar-2025
Supersedes date 25-Oct-2021

Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products

Hazardous decomposition products Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

Section 11: Toxicological information

Acute toxicity

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye damage. May cause irreversible damage to eyes.

Skin contact Specific test data for the substance or mixture is not available. May cause sensitization by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Causes mild skin irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms Redness. Burning. May cause blindness. Itching. Rashes. Hives. Prolonged contact may cause redness and irritation.

Acute toxicity

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATE _{mix} (oral)	5,000.00 mg/kg
ATE _{mix} (dermal)	12,104.40 mg/kg
ATE _{mix} (inhalation-gas)	>20000 ppm

SAFETY DATA SHEET

BOSTIK SILICONE INDUSTRIAL GRADE CLEAR
Revision Number 2

Revision date 14-Mar-2025
Supersedes date 25-Oct-2021

ATEmix (inhalation-vapor) >20 mg/l
ATEmix (inhalation-dust/mist) 63.80 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
2-Butanone, O,O',O''-(methylsilyldiyl)trioxime	LD50 = 2463 mg/Kg (Rattus) (OECD 401)	LD50 >2000 mg/Kg (Rattus) (OECD 402)	-
Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime	LD50 > 2000 mg/kg (Rattus) OECD 425	LD50 > 2009 mg/kg (Rattus) OECD 402	-
N-(3-(trimethoxysilyl)propyl)ethylenediamine	=2295 mg/kg (Rattus)	>2000 mg/Kg (Rattus)	LC50 4H (Aerosol) 1.5 - 2.44 mg/L air
2-Butanone, oxime	=100 mg/kg (ATE)	1000 - 1800 mg/kg (Oryctolagus cuniculus)	>4.83 mg/L (Rattus) 4 h
Dibutyltin dilaurate	=2071 mg/kg (Rattus) OECD 401	> 2000 mg/kg (Rattus)	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation. Classification based on data available for ingredients. Causes mild skin irritation.

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit				Mild skin irritant

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes burns. Causes serious eye damage.

Component Information

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			Eye Damage

Respiratory or skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)

Method	Species	Results
OECD Test No. 471: Bacterial Reverse Mutation Test	Mammalian cells in vitro	Negative
OECD Test No. 476: In Vitro Mammalian Cell Gene Mutation Tests using the Hprt and xprt genes	Mammalian cells in vitro	Negative

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. Suspected of causing cancer.

2-Butanone, oxime (96-29-7)

SAFETY DATA SHEET

BOSTIK SILICONE INDUSTRIAL GRADE CLEAR
Revision Number 2

Revision date 14-Mar-2025
Supersedes date 25-Oct-2021

Method	Species	Results
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat	Carcinogenic

Reproductive toxicity Based on available data, the classification criteria are not met.

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)

Method	Species	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat Oral	NOAEL >500 mg/Kg

STOT - single exposure May cause damage to organs.

Narcotic effects No information available.

STOT - repeated exposure Based on available data, the classification criteria are not met.

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Subacute oral toxicity gavage		28 days	NOAEL >500 mg/kg

Aspiration hazard Based on available data, the classification criteria are not met.

Section 12: Ecological information

Ecotoxicity

Ecotoxicity

Aquatic ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Crustacea
2-Butanone, O,O',O''-(methylsilyldiyl)trioxime	EC50 (72h) = 94 mg/L (Pseudokirchneriella subcapitata) OECD 201	EC50 (96h) >120 mg/L (Oncorhynchus mykiss) Freshwater static (OECD guideline 203)	EC50 (48h) > 120 mg/L (Daphnia magna) OECD 202
Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime	EC50 (72h) = 16 mg/L (Pseudokirchneriella subcapitata) OECD 201	LC50 (96h) > 120 mg/L (Oncorhynchus mykiss) OECD 203	EC50 (48h) > 120 mg/L (Daphnia magna) OECD 202
N-(3-(trimethoxysilyl)propyl)ethylenediamine	-	LC50 (96h) = 597 mg/L (Danio rerio) Semi-static	EC50 (48h) = 81 mg/L Daphnia magna Static
2-Butanone, oxime	EC50: = 83 mg/L (72h, Desmodesmus subspicatus)	LC50: = 760 mg/L (96h, Poecilia reticulata) LC50: 777 - 914 mg/L (96h, Pimephales promelas) LC50: 320 - 1000 mg/L (96h, Leuciscus idus)	EC50: = 750 mg/L (48h, Daphnia magna)
Dibutyltin dilaurate	EC50 1 (72h) mg/L (desmodesmus subspicatus)	LC50: = 2 mg/L (48h, Oryzias latipes)	0,463 (48h) mg/L (daphnia magna)

SAFETY DATA SHEET

BOSTIK SILICONE INDUSTRIAL GRADE CLEAR
Revision Number 2

Revision date 14-Mar-2025
Supersedes date 25-Oct-2021

Terrestrial ecotoxicity There is no data for this product.

Persistence and degradability No information available.

Bioaccumulative potential
Bioaccumulation
Component Information

Chemical name	Partition coefficient
2-Butanone, O,O',O''-(methylsilyldiyl)trioxime	1.69
Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime	1.69
N-(3-(trimethoxysilyl)propyl)ethylenediamine	-0.3
2-Butanone, oxime	0.65
Dibutyltin dilaurate	4.44

Mobility in soil

Mobility No information available.

Other adverse effects

No information available.

Disposal methods

Waste from residues/unused products

Dispose of product in packaging in a way that is consistent with the EPA Consolidation 30 April 2021 of the Hazardous Substances (Disposal) Notice 2017 and the Act. Treat the substance using a method that changes the characteristics or composition of the substance so that the substance is no longer a hazardous substance; or export the substance from New Zealand as waste. Substances which are hazardous to human health or corrosive to metals – may be discharged into the environment if a tolerable exposure limit has been set for the substance (or a component of that substance); and the discharge does not, after reasonable mixing, result in the concentration of the substance in an environmental medium exceeding the tolerable exposure limit. If there is no tolerable exposure limit for the substance, then it may only be discharged into the environment if the substance is very rapidly converted to substances that are not hazardous substances. Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

Section 14: Transport information

IATA Not regulated

IMDG Not regulated

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

ADR Not regulated

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

EPA New Zealand HSNO approval HSR002679 - Surface Coatings and Colourants (Carcinogenic)

SAFETY DATA SHEET

BOSTIK SILICONE INDUSTRIAL GRADE CLEAR
Revision Number 2

Revision date 14-Mar-2025
Supersedes date 25-Oct-2021

code or group standard

National regulations

There are no applicable tolerable exposure limits or environmental exposure limits according to the EPA Controls for Hazardous Substances

Certified handlers, tracking and controlled substance license requirements

Certified handlers are required for some substances. This includes substances requiring a controlled substance license, and most explosives, vertebrates toxic agents, and certain fumigants. Acutely toxic substances which are a Category 1 or 2, such as pesticides also require Certified handlers. Please check the Health and Safety at Work Act 2015 for further information

Tracking is required for some highly hazardous substances. These substances need to be under the control of an appropriately trained person or appropriately secured. Please check the Health and Safety at Work Act 2015 for further information

Controlled substance licenses are required to possess certain explosives, vertebrate toxic agents and fumigants. See Part 7 of the Health and Safety at Work Regulation 2017 for more information

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Europe

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Section 16: Other information

Prepared By Product Stewardship and Regulatory Affairs
Revision date 14-Mar-2025

Revision Note

***Indicates updated data since last publication.

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

SVHC: Substances of Very High Concern for Authorization:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances

vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity

ATE: Acute Toxicity Estimate

LC50: 50% Lethal Concentration

LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average)

STEL

STEL (Short Term Exposure Limit)

Ceiling Maximum limit value

Sk*

Skin designation

** Hazard Designation

+

Sensitizers

C Carcinogen

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)

U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA)

SAFETY DATA SHEET

BOSTIK SILICONE INDUSTRIAL GRADE CLEAR
Revision Number 2

Revision date 14-Mar-2025
Supersedes date 25-Oct-2021

Environmental Protection Agency
Acute Exposure Guideline Level(s) (AEGl(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine's PubMed database (NLM PUBMED)
U.S. National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
Organization for Economic Co-operation and Development High Production Volume Chemicals Program
Organization for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet