



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Hazardous Substances (Safety Data Sheets) Notice 2017 EPA Consolidation 30
September 2022

BOSTIK TRIPLE 5 BSR RED
Revision Number 1

Revision date 11-Dec-2024
Supersedes date 17-Mar-2022

Section 1: Identification

Product identifier

Product Name BOSTIK TRIPLE 5 BSR RED

Other means of identification

Recommended use of the chemical and restrictions on use

Recommended use Contact adhesives

Uses advised against Consumer use

Details of the supplier of the safety data sheet

Supplier

Bostik New Zealand Limited
19 Eastern Hutt Road Wingate,
Lower Hutt, New Zealand
Tel: 04-567 5119
Fax: 04-567 5412

Manufacturer

Bostik New Zealand Limited
19 Eastern Hutt Road Wingate,
Lower Hutt, New Zealand
Tel: 04-567 5119
Fax: 04-567 5412

E-mail address SDS.AP@Bostik.com

Emergency telephone number

Emergency Telephone 24 Hr: 0800 243 622
International +64 4 917 9888
Poison Centre : 0800 764 766

Section 2: Hazard identification

GHS Classification

Flammable liquids	Category 2
Aspiration hazard	Category 1
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Hazardous to the aquatic environment - acute	Category 1
Hazardous to the aquatic environment - chronic	Category 1

Label elements



SAFETY DATA SHEET

BOSTIK TRIPLE 5 BSR RED
Revision Number 1

Revision date 11-Dec-2024
Supersedes date 17-Mar-2022

Signal word
Danger

Hazard statements

H225 - Highly flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H361 - Suspected of damaging fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure
H410 - Very toxic to aquatic life with long lasting effects

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wash face, hands and any exposed skin thoroughly after handling
Contaminated work clothing should not be allowed out of the workplace
Use only outdoors or in a well-ventilated area
Do not breathe dust
Avoid release to the environment
Ground and bond container and receiving equipment
Use non-sparking tools
Take action to prevent static discharges
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Keep container tightly closed
Keep cool
Wear protective gloves
Use explosion-proof electrical/ ventilating/ lighting/ equipment

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

Skin

If skin irritation or rash occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor

Do NOT induce vomiting

Fire

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Spill

Collect spillage

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable

Other hazards which do not result in classification

May be harmful if inhaled. In use, may form flammable/explosive vapor-air mixture.

Section 3: Composition/information on ingredients

SAFETY DATA SHEET

BOSTIK TRIPLE 5 BSR RED
Revision Number 1

Revision date 11-Dec-2024
Supersedes date 17-Mar-2022

Chemical name	CAS No.	Weight-%
Acetone	67-64-1	20- <40
Heptane	142-82-5	20- <40
Toluene	108-88-3	10 - <20
Cyclohexane	110-82-7	5 - <10
Methylcyclopentane	96-37-7	1 - <3
Octane	111-65-9	1 - <3
Tall oil rosin	8052-10-6	0.1- <1
Zinc oxide	1314-13-2	0.1- <1
4-tert-Butylphenol	98-54-4	0.1- <1

Non-hazardous ingredients	Proprietary	Balance
---------------------------	-------------	---------

Section 4: First-aid measures

Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Inhalation	Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate medical attention.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms	Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
Effects of Exposure	May cause adverse reproductive effects - such as birth defect, miscarriages, or infertility. May cause damage to organs through prolonged or repeated exposure.

Indication of any immediate medical attention and special treatment needed

Note to physicians	May cause sensitization in susceptible persons. Treat symptomatically. Because of the
---------------------------	---

SAFETY DATA SHEET

BOSTIK TRIPLE 5 BSR RED
Revision Number 1

Revision date 11-Dec-2024
Supersedes date 17-Mar-2022

danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.

Section 5: Fire-fighting measures

Suitable Extinguishing Media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO₂). Water spray. Alcohol resistant foam.

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the chemical

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Product is or contains a sensitizer. May cause sensitization by skin contact.

Hazardous combustion products Carbon oxides. Hydrocarbons. Hydrogen chloride. Aldehydes.

Special protective actions for fire-fighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Precautions to prevent secondary hazards

SAFETY DATA SHEET

BOSTIK TRIPLE 5 BSR RED
Revision Number 1

Revision date 11-Dec-2024
Supersedes date 17-Mar-2022

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: Handling and storage

Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Remove contaminated clothing and shoes.

General hygiene considerations

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials. Protect from moisture.

Recommended storage temperature

Keep at temperatures between 41 and 77 °F / 5 and 25 °C.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

Section 8: Exposure controls/personal protection

Working area parameters, subject to mandatory control (MAC or TSEL)

Exposure Limits

This product contains substances which in their raw state are powder form, however in this product they are in a non-respirable form. Inhalation of powder/dust particles is unlikely to occur from exposure to this product.

Chemical name	New Zealand	ACGIH TLV	United Kingdom	Australia
Acetone 67-64-1	TWA: 500 ppm; TWA: 1185 mg/m ³ ; STEL: 1000 ppm; STEL: 2375 mg/m ³ ;	TWA: 250 ppm STEL: 500 ppm	TWA: 500 ppm; TWA: 1210 mg/m ³ ; STEL: 1500 ppm; STEL: 3620 mg/m ³ ;	TWA: 500 ppm; TWA: 1185 mg/m ³ ; STEL: 1000 ppm; STEL: 2375 mg/m ³ ;
Heptane 142-82-5	TWA: 400 ppm; TWA: 1640 mg/m ³ ; STEL: 500 ppm; STEL: 2050 mg/m ³ ;	TWA: 400 ppm STEL: 500 ppm	TWA: 500 ppm; TWA: 2085 mg/m ³ ; STEL: 1500 ppm; STEL: 6255 mg/m ³ ;	TWA: 400 ppm; TWA: 1640 mg/m ³ ; STEL: 500 ppm; STEL: 2050 mg/m ³ ;
Toluene 108-88-3	TWA: 20 ppm; TWA: 75 mg/m ³ ;	TWA: 20 ppm pOt	TWA: 50 ppm; TWA: 191 mg/m ³ ;	TWA: 50 ppm; TWA: 191 mg/m ³ ;

SAFETY DATA SHEET

BOSTIK TRIPLE 5 BSR RED
Revision Number 1

Revision date 11-Dec-2024
Supersedes date 17-Mar-2022

	STEL: 100 ppm; STEL: 377 mg/m ³ ; dSk		STEL: 100 ppm; STEL: 384 mg/m ³ ; pSk	STEL: 150 ppm; STEL: 574 mg/m ³ ;
Cyclohexane 110-82-7	TWA: 100 ppm; TWA: 350 mg/m ³ ; STEL: 300 ppm; STEL: 1050 mg/m ³ ;	TWA: 100 ppm	TWA: 100 ppm; TWA: 350 mg/m ³ ; STEL: 300 ppm; STEL: 1050 mg/m ³ ;	TWA: 100 ppm; TWA: 350 mg/m ³ ; STEL: 300 ppm; STEL: 1050 mg/m ³ ;
Octane 111-65-9	TWA: 300 ppm; TWA: 1400 mg/m ³ ; STEL: 375 ppm; STEL: 1750 mg/m ³ ;	TWA: 300 ppm	-	TWA: 300 ppm; TWA: 1400 mg/m ³ ; STEL: 375 ppm; STEL: 1750 mg/m ³ ;
Zinc oxide 1314-13-2	TWA: 0.1 mg/m ³ ; respirable dust TWA: 2 mg/m ³ ; respirable dust STEL: 0.5 mg/m ³ ; respirable dust STEL: 5 mg/m ³ ; respirable dust	TWA: 2 mg/m ³ respirable particulate matter STEL: 10 mg/m ³ respirable particulate matter	-	TWA: 10 mg/m ³ ; inhalable dust TWA: 5 mg/m ³ ; fume STEL: 10 mg/m ³ ; fume

Biological occupational exposure limits

Chemical name	New Zealand	ACGIH
Acetone 67-64-1	50 mg/L - urine (Acetone) - end of shift	25 mg/L - urine (Acetone) - end of shift
Toluene 108-88-3	0.03 mg/L - urine (Toluene) - end of exposure or end of shift 0.3 mg/g creatinine - urine (O-Cresol) - end of exposure or end of shift	0.02 mg/L - blood (Toluene) - prior to last shift of workweek 0.03 mg/L - urine (Toluene) - end of shift 0.3 mg/g creatinine - urine (o-Cresol with hydrolysis) - end of shift
Cyclohexane 110-82-7	-	50 mg/g creatinine - urine (1,2-Cyclohexanediol) - end of shift at end of workweek

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Wear suitable gloves. Impervious gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.
Antistatic boots.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state Liquid
Appearance Liquid

SAFETY DATA SHEET

BOSTIK TRIPLE 5 BSR RED
Revision Number 1

Revision date 11-Dec-2024
Supersedes date 17-Mar-2022

Color Red
Odor Aromatic. Solvent.
Odor threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	Not applicable Insoluble in water
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	50 °C	
Flash point	-22 °C	
Evaporation rate	No data available	None known
Flammability	No data available	Flammable liquid
Flammability Limit in Air		None known
Upper flammability or explosive limits	9.7	
Lower flammability or explosive limits	1.5	
Vapor pressure	<110 kPa	None known
Relative vapor density	No data available	None known
Relative density	No data available	None known
Water solubility	Insoluble in water	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	
Explosive properties	No information available.	
Oxidizing properties	No information available.	
<u>Other information</u>		
Softening point	No information available	
Molecular weight	No information available	
VOC content	No information available	
Density	0.84 g/cm ³	
Bulk density	No information available	
Particle characteristics		

Section 10: Stability and reactivity

Reactivity

Reactivity No information available.

Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Heat, flames and sparks. Protect from moisture.

SAFETY DATA SHEET

BOSTIK TRIPLE 5 BSR RED
Revision Number 1

Revision date 11-Dec-2024
Supersedes date 17-Mar-2022

Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

Hazardous decomposition products

Hazardous decomposition products Carbon oxides.

Section 11: Toxicological information

Acute toxicity

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness. May be harmful if inhaled.
Eye contact	Specific test data for the substance or mixture is not available. May cause irritation. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	May cause sensitization by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Repeated exposure may cause skin dryness or cracking. Causes skin irritation.
Ingestion	Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Acute toxicity

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral)	>5000 mg/kg
ATEmix (dermal)	>5000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-vapor)	>20 mg/l
ATEmix (inhalation-dust/mist)	146.013 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone	=5800 mg/kg (Rattus) 3000 mg/Kg (mouse)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
Heptane	LD50 > 5000 mg/Kg (rattus)	= 3000 mg/kg (Oryctolagus cuniculus)	=103 g/m ³ (Rattus) 4 h
Toluene	=5580 mg/kg (Rattus)	= 12000 mg/kg (Oryctolagus	>20 mg/L (Rattus) 4 h

SAFETY DATA SHEET

BOSTIK TRIPLE 5 BSR RED
Revision Number 1

Revision date 11-Dec-2024
Supersedes date 17-Mar-2022

Cyclohexane	=12705 mg/kg (Rattus)	cuniculus) > 2000 mg/kg (Oryctolagus cuniculus)	>9500 ppm (Rattus) 4 h
Octane	>5000 mg/Kg (Rattus)	-	=118 g/m ³ (Rattus) 4 h = 25260 ppm (Rattus) 4 h > 23.36 mg/L (Rattus) 4 h
Tall oil rosin	=7600 mg/kg (Rattus)	-	-
Zinc oxide	>5000 mg/kg (Rattus)	LD50 >2000 mg/Kg (Rattus) (OECD 402)	LC50 (4h) >5.7 mg/l
4-tert-Butylphenol	=4000 mg/kg (Rattus)	LD50 >5000 mg/kg (Oryctolagus cuniculus) OECD 402	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Toluene (108-88-3)

Method	Species	Exposure route	Effective dose	Exposure time	Results
Regulation (EC) No. 440/2008, Annex, B.4	Rabbit	Dermal			Irritant

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Component Information

Acetone (67-64-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			irritant

Respiratory or skin sensitization May cause an allergic skin reaction.

Acetone (67-64-1)

Method	Species	Exposure route	Results
GPMT - Guinea pig maximisation test	Guinea pig	Dermal	Not a skin sensitizer

Toluene (108-88-3)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Heptane (142-82-5)

Method	Species	Results
OECD Test No. 473: In vitro Mammalian Chromosome Aberration Test	Rat, in vitro	Not mutagenic
OECD Test No. 471: Bacterial Reverse Mutation Test		Not mutagenic in AMES Test

Toluene (108-88-3)

Method	Species	Results
Regulation (EC) No. 440/2008, Annex, B.13/14 (Ames test)	Salmonella typhimurium	Not mutagenic
OECD Test No. 476: In Vitro Mammalian Cell Gene Mutation Tests using the Hprt and xprt genes	Mouse	Not mutagenic

SAFETY DATA SHEET

BOSTIK TRIPLE 5 BSR RED
Revision Number 1

Revision date 11-Dec-2024
Supersedes date 17-Mar-2022

Carcinogenicity

This product contains substances which in their raw state are powder form, however in this product they are in a non-respirable form. Inhalation of powder/dust particles is unlikely to occur from exposure to this product.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	New Zealand	IARC
Toluene - 108-88-3	-	Group 3

Legend

IARC (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicity

Contains a known or suspected reproductive toxin. Classification based on data available for ingredients. Suspected of damaging fertility or the unborn child.

Toluene (108-88-3)

Method	Species	Results
OECD 407	in vivo	Reproductive toxicant

STOT - single exposure

May cause drowsiness or dizziness.

Acetone (67-64-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
Experiences made in practice					Narcotic effects

Narcotic effects

Narcotic effects.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Acetone (67-64-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 408: Repeated Dose 90-Day Oral Toxicity Study in Rodents	Rat	Oral	200-3400 mg/kg bw/day	91 days	No Observed Adverse Effect Level LOAEL 1700 mg/kg bw/day
Not specified	Rat	Inhalation	19000 ppm	14, 28, 56 days	NOAEC 19000 ppm No Observed Adverse Effect Level

Toluene (108-88-3)

Method	Species	Exposure route	Effective dose	Exposure time	Results
Regulation (EC) No. 440/2008, Annex, B.26	Rat, male, female	Oral		91 days	NOAEL: 625 mg/kg
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat, male, female	Inhalation, vapor			NOAEL: 1.131 mg/l

Aspiration hazard

May be fatal if swallowed and enters airways.

Section 12: Ecological information

Ecotoxicity

SAFETY DATA SHEET

BOSTIK TRIPLE 5 BSR RED
Revision Number 1

Revision date 11-Dec-2024
Supersedes date 17-Mar-2022

Ecotoxicity Very toxic to aquatic life with long lasting effects.

Aquatic ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Crustacea
Acetone	-	LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss)	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)
Heptane	-	LC50: =375.0mg/L (96h, Cichlid)	EC50: >10mg/L (24h, Daphnia magna)
Toluene	EC50 72 h = 12.5 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h 5.89 - 7.81 mg/L (Oncorhynchus mykiss flow-through) LC50 96 h = 5.8 mg/L (Oncorhynchus mykiss semi-static)	EC50: =11.5mg/L (48h, Daphnia magna) EC50: 5.46 - 9.83mg/L (48h, Daphnia magna)
Cyclohexane	EC50 72 h > 9.3 mg/L (Pseudokirchneriella subcapitata)	LC50: 23.03 - 42.07mg/L (96h, Pimephales promelas) LC50: 48.87 - 68.76mg/L (96h, Poecilia reticulata) LC50: 3.96 - 5.18mg/L (96h, Pimephales promelas) LC50: 24.99 - 44.69mg/L (96h, Lepomis macrochirus)	EC50: >0.9 mg/L (24h, Daphnia magna)
Octane	-	-	EC50: =0.38mg/L (48h, Daphnia magna)
Tall oil rosin	EC50: 185 - 217mg/L (72h, Pseudokirchneriella subcapitata)	LC50: 100 - 200mg/L (96h, Brachydanio rerio)	EC50: 238 - 479mg/L (48h, Daphnia magna)
Zinc oxide	LC 50 (72Hr) 0.136 mg/L	LC50 (96h) =0.7 mg/L (Danio rerio)	LC 50 (48Hr) =0.5 mg/l (Ceriodaphnia dubia)
4-tert-Butylphenol	EC50: =11.2mg/L (72h, Desmodesmus subspicatus)	LC50: =6.9mg/L (96h, Cyprinus carpio) LC50: 4.71 - 5.62mg/L (96h, Pimephales promelas)	EC50: 3.4 - 4.5mg/L (48h, Daphnia magna) EC50: =3.9mg/L (48h, Daphnia magna)

Terrestrial ecotoxicity

Chemical name	Earthworm	Avian	Honeybees
Acetone	Acute Toxicity: LC50 200 - 1000 µg/cm ² (Eisenia foetida, 48 h filter paper)	Dietary Toxicity: LC50 > 40000 ppm (Phasianus colchicus, 5 Days) Dietary Toxicity: LC50 > 40000 ppm (Coturnix coturnix japonica, 5 Days)	-

Persistence and degradability No information available.

Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Acetone	-0.24
Heptane	4.66
Toluene	2.73
Cyclohexane	3.44
Octane	5.18
Tall oil rosin	3.6
4-tert-Butylphenol	3

Mobility in soil

Mobility No information available.

Other adverse effects

SAFETY DATA SHEET

BOSTIK TRIPLE 5 BSR RED
Revision Number 1

Revision date 11-Dec-2024
Supersedes date 17-Mar-2022

Disposal methods

Waste from residues/unused products

Dispose of product in packaging in a way that is consistent with the EPA Consolidation 30 April 2021 of the Hazardous Substances (Disposal) Notice 2017 and the Act. Treat the substance using a method that changes the characteristics or composition of the substance so that the substance is no longer a hazardous substance; or export the substance from New Zealand as waste. Flammable substances - may not be disposed of into or onto a landfill or sewage facility.

They may only be burnt in certain situations.

Flammable gases, liquids and solids may only be discharged into the environment or landfill as waste if the substance will not at any time come into contact with any explosives, oxidising gases, liquids or solids or organic peroxides; and there will be no ignition source in the vicinity of the disposal site at any time and if the substance were to ignite, no person, or place where a person may legally be, would be exposed to an unsafe level of heat radiation. Substances which are hazardous to human health or corrosive to metals – may be discharged into the environment if a tolerable exposure limit has been set for the substance (or a component of that substance); and the discharge does not, after reasonable mixing, result in the concentration of the substance in an environmental medium exceeding the tolerable exposure limit. If there is no tolerable exposure limit for the substance, then it may only be discharged into the environment if the substance is very rapidly converted to substances that are not hazardous substances. Environmentally hazardous substances – if the substance, or if it contains a component that is hazardous to the aquatic environment or bioaccumulative and not rapidly degradable, then any component that is bioaccumulative and not rapidly degradable must be removed. The product may only be discharged into the environment if an environmental exposure limit has been set for the substance (or a component of the substance); and the discharge does not, after reasonable mixing, result in the concentration of the substance in an environmental medium exceeding the environmental exposure limit.

Contaminated packaging

For packages that have been in direct contact with hazardous substances, the person must ensure that the package is rendered incapable of containing any substance. It must be disposed of in a manner that is consistent with the requirements for disposal of the substance that it contained, taking into account the material the package is manufactured from. Packages may only be reused or recycled if:

- the substance has a physical hazard other than corrosive to metal, and has been treated to remove any residual contents of the hazardous substance;
- or for substances that have a health or environmental hazard, or corrosive to metal, the contents of the residue in the package are below the threshold for the substance to be classified as hazardous in the Hazardous Substances (Hazard Classification) Notice 2020.

Section 14: Transport information

IATA

UN number or ID number	UN1133
UN proper shipping name	Adhesives
Transport hazard class(es)	3
Packing group	II
Special Provisions	A3
Description	UN1133, Adhesives, 3, II

IMDG

UN number or ID number	UN1133
UN proper shipping name	Adhesives
Transport hazard class(es)	3
Packing group	II
EmS-No.	F-E, S-D

SAFETY DATA SHEET

BOSTIK TRIPLE 5 BSR RED
Revision Number 1

Revision date 11-Dec-2024
Supersedes date 17-Mar-2022

Marine pollutant P
Description UN1133, Adhesives, 3, II, (-22°C c.c.), Marine pollutant

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
No information available

ADR

UN number or ID number UN1133
UN proper shipping name Adhesives
Transport hazard class(es) 3
Labels 3
Packing group II
Description UN1133, Adhesives, 3, II, (D/E), Environmentally Hazardous
Environmental hazards Yes
Limited quantity (LQ) 5 L
Special Provisions 640D
Classification code F1
Tunnel restriction code (D/E)

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

EPA New Zealand HSNO approval code or group standard HSR002662 - Surface Coatings and Colourants (Flammable)

National regulations Any applicable tolerable exposure limits and environmental exposure limits according to the EPA Controls for Hazardous Substances are listed below

Chemical name	Tolerable Exposure Limit (TEL) Air	Tolerable Exposure Limit (TEL) Water	Tolerable Exposure Limit (TEL) Surface	Environmental Exposure Limits (EEL)
Toluene 108-88-3	400 µg/m ³	0.8 mg/L	-	330 µg/L (Water)
Zinc oxide 1314-13-2	0.87 mg/m ³	0.6 mg/L	-	8 µg/L (Freshwater) 15 µg/L (Marine)

Certified handlers, tracking and controlled substance license requirements

Certified handlers are required for some substances. This includes substances requiring a controlled substance license, and most explosives, vertebrates toxic agents, and certain fumigants. Acutely toxic substances which are a Category 1 or 2, such as pesticides also require Certified handlers. Please check the Health and Safety at Work Act 2015 for further information
Tracking is required for some highly hazardous substances. These substances need to be under the control of an appropriately trained person or appropriately secured. Please check the Health and Safety at Work Act 2015 for further information
Controlled substance licenses are required to possess certain explosives, vertebrate toxic agents and fumigants. See Part 7 of the Health and Safety at Work Regulation 2017 for more information

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

SAFETY DATA SHEET

BOSTIK TRIPLE 5 BSR RED
Revision Number 1

Revision date 11-Dec-2024
Supersedes date 17-Mar-2022

Europe

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorization:

This product contains one or more candidate substance(s) of very high concern (Regulation (EC) No. 1907/2006 (REACH), Article 59) $\geq 0.1\%$

Chemical name	SVHC candidates
4-tert-Butylphenol 98-54-4	X

Section 16: Other information

Prepared By Product Stewardship and Regulatory Affairs
Revision date 11-Dec-2024

Revision Note

***Indicates updated data since last publication.

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances
STOT: Specific Target Organ Toxicity
ATE: Acute Toxicity Estimate
LC50: 50% Lethal Concentration
LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	Sk*	Skin designation
**	Hazard Designation	+	Sensitizers
C	Carcinogen		

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
Environmental Protection Agency
Acute Exposure Guideline Level(s) (AEGl(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine's PubMed database (NLM PUBMED)
U.S. National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
Organization for Economic Co-operation and Development High Production Volume Chemicals Program
Organization for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing,

SAFETY DATA SHEET

BOSTIK TRIPLE 5 BSR RED
Revision Number 1

Revision date 11-Dec-2024
Supersedes date 17-Mar-2022

storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet