

# TECHNICAL DATA SHEET

# GEKKO G50

## ZERO FLAM CONTACT ADHESIVE



THE GEKKO G50 CANISTER SYSTEM IS DESIGNED FOR BONDING A VARIETY OF SUBSTRATES TO SUBFLOORS. UNIQUE IN ITS CLASS, GEKKO G50 USES ZERO-FLAM™ TECHNOLOGY WHICH INCORPORATES NON-FLAMMABLE PROPELLANT AS WELL AS NON-FLAMMABLE ADHESIVE. AS A RESULT, GEKKO G50 CAN BE USED IN AREAS WHERE FLAMMABLE PRODUCTS CANNOT BE USED.

The unique portable, fully contained canister system allows you to stand up and apply the adhesive. This will reduce knee injury, reduce labour time and increase efficiency, resulting in increased profitability for the installer.

The benefits of ZERO-FLAM™ technology makes Gekko G50 a real solution for bonding applications in occupied areas.

### BENEFITS:

- Non flammable
- Fast drying with a long open time
- Portable, quick & easy application
- 230 sprayed square metres per 22ltr canister
- Economic
- High temperature resistance

### TECHNICAL DATA

Colour:	Clear
Flammability:	Non Flam Adhesive & Propellant
Dry time:	1-2Mins Depending On Temp & Humidity
Open time:	1 Hour
Coverage (sprayed):	230Sqm Per 22Ltr
Temperature resistance:	105 °C

### SIZES AVAILABLE

22ltr canister



