

## 1. Identification of Substance & Company

### Product

|                             |                                                                                                                                                                                                         |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product name</b>         | STRONGBOND LEVELLING & REPAIR SB032                                                                                                                                                                     |
| <b>Product code</b>         | 22062                                                                                                                                                                                                   |
| <b>HSNO approval</b>        | HSR002545,                                                                                                                                                                                              |
| <b>Approval description</b> | Construction Products (Carcinogenic) Group Standard 2020                                                                                                                                                |
| <b>UN number</b>            | NA                                                                                                                                                                                                      |
| <b>Proper Shipping Name</b> | NA                                                                                                                                                                                                      |
| <b>DG class</b>             | NA                                                                                                                                                                                                      |
| <b>Packaging group</b>      | NA                                                                                                                                                                                                      |
| <b>Hazchem code</b>         | NA                                                                                                                                                                                                      |
| <b>Uses</b>                 | An advanced dual-purpose compound that combines the versatility of a self-levelling compound that can also be used as a repair mortar, providing a highly versatile solution for substrate preparation. |

### Company Details

|                  |                                                              |
|------------------|--------------------------------------------------------------|
| <b>Company</b>   | <b>Flooring Wholesale Limited T/A Look Floors</b>            |
| <b>Address</b>   | 9 Industry Road,<br>Penrose,<br>Auckland 1061<br>New Zealand |
| <b>Telephone</b> | 0800 10 26 26                                                |
| <b>Email</b>     | solutions@lookfloors.co.nz                                   |
| <b>Website</b>   | www.lookfloors.co.nz                                         |

**Emergency Telephone Number: 0800 764 766**

## 2. Hazard Identification

### Approval

This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO, Approval HSR002545, Construction Products (Carcinogenic) Group Standard 2020). The substance has been classified as hazardous according to the criteria in the Hazardous substances (Hazard Classification) Notice 2020.

### GHS 7 Classes

### Hazard Statements

|                                    |                                                                        |
|------------------------------------|------------------------------------------------------------------------|
| Eye damage category 1              | H318 - Causes serious eye damage.                                      |
| Skin irritant category 2           | H315 - Causes skin irritation.                                         |
| Carcinogen category 1              | H350 - May cause cancer.                                               |
| STOT* repeated exposure category 1 | H372 - Causes damage to organs through prolonged or repeated exposure. |

\*STOT – System Target Organ Toxicity

*This substance is considered irritating to the skin under the classification system; however, there is a possibility of burns if wet cement or cement mixture is left in contact with the skin for a prolonged time.*

*This substance may contain silica (as quartz) in trace amounts. Carcinogen cat 1 and STOT RE cat 1 apply if quartz silica is present as a fine respirable dust.*

### SYMBOLS

**DANGER**



#### Other Classifications

There are no other classifications that are known to apply.

#### Precautionary Statements

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Prevention</b> | P101 - If medical advice is needed, have product container or label at hand.<br>P102 - Keep out of reach of children.<br>P103 - Read label before use.<br>P201 - Obtain special instructions before use.<br>P202 - Do not handle until all safety precautions have been read and understood.<br>P260 - Do not breathe dust/fume/gas/mist/vapours/spray.<br>P264 - Wash hands thoroughly after handling.<br>P270 - Do not eat, drink or smoke when using this product."<br>P273 - Avoid release to the environment.<br>P280 - Wear protective gloves/eye protection.<br>P280 - Wear protective gloves/protective clothing. |
| <b>Response</b>   | P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.<br>P310 - Immediately call a POISON CENTRE or doctor.<br>P302+P352 - IF ON SKIN: Wash with plenty of soap and water.<br>P332+P313 - If skin irritation occurs: Get medical advice/ attention.<br>P362 - Take off contaminated clothing and wash before re-use.<br>P308+P313 - IF exposed or concerned: Get medical advice/ attention.                                                                                                                                   |
| <b>Storage</b>    | P405 - Store locked up                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Disposal</b>   | P501 - Dispose of contents/container in accordance with local/regional/national/international regulation.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

### 3. Composition / Information on Ingredients

| Component                       | CAS/ Identification | Conc (%) |
|---------------------------------|---------------------|----------|
| Cement (sulphoaluminate cement) | 12004-14-7          | 40%      |
| Crystalline silica (Quartz)     | 14808-60-7          | 60%      |

This is a commercial product whose exact ratio of components may vary slightly. Trace quantities of impurities are also likely.

### 4. First Aid

#### General Information

If medical advice is needed, have product container or label at hand. You should call the National Poisons Centre if you feel that you may have been harmed or irritated by this product. The number is 0800 764 766 (0800 POISON) (24 hr emergency service).

**Recommended first aid facilities** Ready access to running water is recommended. Accessible eyewash is recommended.

#### Exposure

|                     |                                                                                                                                                                                                                                                                                                                              |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Swallowed</b>    | IF SWALLOWED: Do NOT induce vomiting. Rinse mouth. Contact a doctor if you feel unwell.                                                                                                                                                                                                                                      |
| <b>Eye contact</b>  | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Apply continuous irrigation with water for at least 15 minutes holding eyelids apart. Immediately call a POISON CENTER or doctor.                                                                             |
| <b>Skin contact</b> | IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.                                                                                                                                                                            |
| <b>Inhaled</b>      | IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If patient is unconscious, place in the recovery position (on the side) for transport and contact a doctor. If experiencing respiratory symptoms: Immediately call a POISON CENTER or doctor/physician. |

#### Advice to Doctor

Treat symptomatically

## 5. Firefighting Measures

|                                             |                                                                                                                                                                                                                               |
|---------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Fire and explosion hazards:</b>          | There are no specific risks for fire/explosion for this chemical. It is non-combustible.                                                                                                                                      |
| <b>Suitable extinguishing substances:</b>   | Carbon dioxide, extinguishing powder or water jet. Fight larger fires with water jet or alcohol resistant foam.                                                                                                               |
| <b>Unsuitable extinguishing substances:</b> | Unknown.                                                                                                                                                                                                                      |
| <b>Products of combustion:</b>              | Product does not burn. Dust may form irritating atmosphere. Product will react exothermically with water. Contaminated water will be strongly alkaline. Product may decompose in a fire and produce toxic or corrosive fumes. |
| <b>Protective equipment:</b>                | Self-contained breathing apparatus. Safety boots, non-flammable overalls, gloves, hat and eye protection.                                                                                                                     |
| <b>Hazchem code:</b>                        | NA                                                                                                                                                                                                                            |

## 6. Accidental Release Measures

|                             |                                                                                                                                                                                                                                                                                                                                                                                   |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Containment</b>          | If greater than 1000kg (wet product or dust) is stored, secondary containment is required. Emergency plans to manage any potential spills must be in place. Prevent spillage from spreading or entering soil, waterways or drains.                                                                                                                                                |
| <b>Emergency procedures</b> | In the event of large spillage (>100kg) of the dry or wetted mixture alert the fire brigade to location and give brief description of hazard.<br>Wear protective equipment to prevent skin, eye and respiratory exposure. Clear area of any unprotected personnel. Contain spill. Prevent by whatever means possible any spillage from entering drains, sewers, or water courses. |
| <b>Clean-up method</b>      | Collect product avoiding any dust formation, and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.                                                                                                                                                                         |
| <b>Disposal</b>             | Mop up and collect recoverable material into labelled containers for recycling or salvage. Recycle containers wherever possible. This material may be suitable for approved landfill. Dispose of only in accord with all regulations.                                                                                                                                             |
| <b>Precautions</b>          | The dust may form irritating atmosphere. Contaminated water will be strongly alkaline. Do not allow contaminated water to enter the environment.<br>Wear protective equipment to prevent skin and eye contamination and the inhalation of dust. Work up wind or increase ventilation.                                                                                             |

## 7. Storage & Handling

|                 |                                                                                                                                                                                                                                                    |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Storage</b>  | Avoid storage of harmful substances with food. Store out of reach of children. Containers should be kept closed in order to minimise contamination. Keep in a cool, dry place. Avoid contact with incompatible substances as listed in Section 10. |
| <b>Handling</b> | Keep exposure to a minimum, and minimise the quantities kept in work areas. Minimise dust generation and accumulation. See section 8 with regard to personal protective equipment requirements. Avoid skin and eye contact and inhalation of dust. |

## 8. Exposure Controls / Personal Protective Equipment

### Workplace Exposure Standards

A workplace exposure standard (WES) has not been established by WorkSafe NZ for this product. There is a general limit of 3mg/m<sup>3</sup> for respirable particulates and 10mg/m<sup>3</sup> for inhalable particulates when limits have not otherwise been established.

| NZ Workplace Exposure Stds | Ingredient                     | WES-TWA                             | WES-STEL |
|----------------------------|--------------------------------|-------------------------------------|----------|
|                            | Crystalline silica, carc cat 1 | 0.025mg/m <sup>3</sup> (respirable) | -        |
|                            | Portland cement, dsen          | 3mg/m <sup>3</sup>                  | -        |
|                            |                                | 1mg/m <sup>3</sup> (respirable)     | -        |

### Engineering Controls

In industrial situations, it is expected that employee exposure to hazardous substances will be controlled to a level as far below the WES as practicable by applying the hierarchy of control required by the Health and Safety at Work Act (2015) and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016. Exposure can be reduced by process modification, use of local exhaust ventilation, capturing substances at the source, or other methods. If you believe air borne concentrations of mists, dusts or vapours are high, you are advised to modify processes or increase ventilation. Exposure levels of crystalline silica should be measured and evaluated by an occupational hygienist.

### Personal Protective Equipment

#### General

Personal Protective Equipment (PPE) should not be used as the primary means of exposure protection, except in the event of an accident or emergency situation or where all other means of protection have proven to inadequate.

Clean PPE after use or dispose of as appropriate. Store PPE for re-use in a clean place. Regular training on the correct use of PPE should be provided. In particular the correct fitting and use of respirators and where applicable the cleaning of respirators should be undertaken.

#### Eyes



Protect eyes with goggles, safety glasses or full face mask. Avoid wearing contact lenses.

#### Skin



Avoid repeated or prolonged skin contact. Wear overalls, waterproof boots and impervious alkali-resistant gloves (e.g., nitrile, PVC, rubber, neoprene). Tuck overalls inside boots and seal with duct tape to reduce risk of concrete entering boots. Remove protective clothing and wash exposed areas with soap and water prior to eating, drinking or smoking. Take special care to ensure that cuts/abrasions or irritated skin are not exposed to this product. It is also important to ensure that wet concrete does not become trapped within gloves, boots or clothing – leaving concrete in contact with the skin for extended period of time may cause skin burns. It is important that skin is also covered when concrete dust is created (e.g., sanding, grinding, crushing or cutting concrete). The dust may also irritate and/or damage the skin.

#### Respiratory

To prevent irritation a well fitted dust mask should be used (this is not recommended when exposure is close to the WES). A fine particulate half or full face respirator with an effective seal is recommended when airborne concentrations approach the WES (section 8). If sanding, grinding, crushing or cutting concrete, it is possible that the silica dust WES (0.01 mg/m<sup>3</sup>) will be exceeded, hence a respirator will be required. If exposure to the concentrated aqueous solution, dust and mist is likely, a full face respirator with a particulate filter is recommended.

### WES Additional Information

Not applicable

## 9. Physical & Chemical Properties

|                                           |               |
|-------------------------------------------|---------------|
| <b>Appearance</b>                         | grey powder   |
| <b>Odour</b>                              | odourless     |
| <b>Odour Threshold</b>                    | no data       |
| <b>pH</b>                                 | 12-13         |
| <b>Freezing/melting point</b>             | no data       |
| <b>Boiling Point</b>                      | >70°C         |
| <b>Flashpoint</b>                         | no data       |
| <b>Flammability</b>                       | non flammable |
| <b>Upper &amp; lower flammable limits</b> | no LEL or UEL |
| <b>Vapour pressure</b>                    | no data       |
| <b>Vapour density</b>                     | no data       |
| <b>Specific gravity/density</b>           | 1.3kg/L       |
| <b>Solubility</b>                         | no data       |
| <b>Partition coefficient</b>              | no data       |
| <b>Auto-ignition temperature</b>          | no data       |
| <b>Decomposition temperature</b>          | no data       |
| <b>Viscosity</b>                          | no data       |
| <b>Particle Characteristics</b>           | no data       |

## 10. Stability & Reactivity

|                                           |                                                                                                                                                                                                 |
|-------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Stability</b>                          | This product is unlikely to react or decompose under normal storage conditions. This product will not undergo polymerisation reactions. Keep dry until used.                                    |
| <b>Conditions to be avoided</b>           | Containers should be kept closed in order to avoid contamination.                                                                                                                               |
| <b>Incompatible groups</b>                | Strong acids, ammonium salts, and aluminum metal.                                                                                                                                               |
| <b>Substance Specific Incompatibility</b> | Concrete dissolves in hydrofluoric acid producing corrosive silicon tetrafluoride gas. Silicates react with powerful oxidizers such as fluorine, chlorine, trifluorides, and oxygen difluoride. |
| <b>Hazardous decomposition products</b>   | Does not readily decompose. Respirable dust particles may be generated when concrete is sawed, drilled, sanded or grinded.                                                                      |
| <b>Hazardous reactions</b>                | Will not polymerise                                                                                                                                                                             |

## 11. Toxicological Information

### Summary

IF SWALLOWED: Swallowing of the dust may result in stomach pains and discomfort and irritation and burns to the mouth, throat and gastrointestinal tract.

IF IN EYES: Contact with wet (unhardened) cement or cement mixtures can cause effects ranging from irritation to serious eye damage/burns and blindness. Note: the level of irritation/damage is dependent on the quantity of the product, the pH, and the length of time exposed. E.g., if product is washed out of the eye immediately, effects will be minor. However, if dust or wet concrete is left in contact with the eye, serious damage/blindness could result.

IF ON SKIN: Contact with wet (unhardened) cement can cause skin irritation or severe chemical burns (third degree). Brief exposure to the skin (i.e., washed off immediately) can result in irritation. However, if the cement or dust is left on the skin for an extended time (e.g., if inside boots or absorbed through overalls), burns to the skin are possible. Thickening of the skin and/or rash is also possible. Contact with dry cement can cause skin irritation.

IF INHALED: there may be irritation of the respiratory tract if dust is inhaled. Short term (acute) silicosis (see "systemic" below) can also occur with one-off exposures to very high levels of fine crystalline silica dust. Other short term effects include irritation, choking and difficulty breathing.

CHRONIC TOXICITY: this product does contain crystalline silica, inhalation of which has been linked to silicosis and lung cancer.). Symptoms include shortness of breath, cough, fever, loss of appetite and cyanosis (bluish skin). See carcinogenicity and systemic toxicity below.

#### Supporting Data

|                |                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|----------------|-------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Acute</b>   | <b>Oral</b>                               | The estimated LD <sub>50</sub> (oral, rat) for the mixture is > 5,000 mg/kg. Ingestion of this product may cause gastrointestinal irritation.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|                | <b>Aspiration</b>                         | This mixture is not considered an aspiration hazard.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|                | <b>Dermal</b>                             | The estimated LD <sub>50</sub> (dermal, rat) for the mixture is > 2000 mg/kg.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|                | <b>Inhaled</b>                            | The estimated LC <sub>50</sub> (inhalation, rat) for the mixture is >5 mg/L (dust mist). Short term (acute) silicosis (see "systemic" below) can also occur with one-off exposures to extremely high levels of fine crystalline silica dust. Other short term effects include irritation, choking and difficulty breathing.                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Chronic</b> | <b>Eye</b>                                | Portland cement triggers Eye damage cat 1 classification. The pH of wet cement is >12.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|                | <b>Skin</b>                               | The dry product is classed as a skin irritant. Wet cement is classed skin corrosive cat 1C, as pH >12.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|                | <b>Sensitisation</b>                      | No ingredient present at concentration >0.1% is considered a sensitizer.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|                | <b>Mutagenicity</b>                       | No ingredient present at concentrations > 0.1% is considered a mutagen.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|                | <b>Carcinogenicity</b>                    | Cement may contain crystalline silica. Crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC Group 1). The mixture triggers carc cat 1 classification (confirmed carcinogen). The carcinogenicity of silica is related to long term (e.g., 10 years) inhalation of very fine particulate (e.g., from sand blasting or dry cutting of concrete). Carcinogenicity of silica appears linked to development of silicosis (see systematic below) followed by complications and, eventually lung cancer.                                                                                                                                                                                                                          |
|                | <b>Reproductive / Developmental</b>       | No data for mixture is available. No ingredient present at concentrations > 0.1% is considered a reproductive or developmental toxicant or have any effects on or via lactation.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|                | <b>Systemic</b>                           | Cement may considered to be a target organ toxicant, because of the presence of crystalline silica at greater than 1%. Crystalline silica triggers STOT RE cat 1 classification if it is in the form of a fine respirable dust in an occupational (chronic exposure) setting. This is due to the development of acute silicosis which can occur following exposure to extremely high levels of fine silica dust. Silicosis is a type of pneumoconiosis – a disease of the lung that causes inflammation, scar tissue, lesions and fibrosis in the lung (alveolar). Symptoms include shortness of breath, cough, fever, loss of appetite and cyanosis (bluish skin). Silicosis can occur following prolonged exposure (e.g., 10 years) to relatively high levels of fine crystalline silica dust. |
|                | <b>Aggravation of existing conditions</b> | Persons with existing lung conditions may be at a higher risk of further adverse health effects (as above). Smokers have an increased risk of lung cancer and silicosis.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |

## 12. Ecological Data

#### Summary

This substance is considered to be harmful in the environment when in a soluble form. This is primarily due to the high pH of the product. Do not allow product to enter drains and waterways.

#### Supporting Data

|                                 |                                                                                                                                                                                                                             |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Aquatic</b>                  | Portland cement is considered ecotoxic towards aquatic organisms due to the high pH when dissolved/suspended in water. Water contaminated with this product is alkaline and should not be allowed to enter the environment. |
| <b>Bioaccumulation</b>          | Not applicable                                                                                                                                                                                                              |
| <b>Degradability</b>            | Not applicable (predominantly natural products)                                                                                                                                                                             |
| <b>Soil</b>                     | No data available for the mixture.                                                                                                                                                                                          |
| <b>Terrestrial vertebrate</b>   | This product is not considered harmful to terrestrial vertebrates – see section 11 – oral toxicity.                                                                                                                         |
| <b>Terrestrial invertebrate</b> | The mixture is not considered harmful to terrestrial invertebrates.                                                                                                                                                         |
| <b>Biocidal</b>                 | Not designed as a biocide.                                                                                                                                                                                                  |

### 13. Disposal Considerations

|                               |                                                                                                                                                                                                                                                                                                                                                                      |
|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Restrictions</b>           | There are no product-specific restrictions, however, local council and resource consent conditions may apply, including requirements of trade waste consents.                                                                                                                                                                                                        |
| <b>Disposal method</b>        | Disposal of this product must comply with the Hazardous Substances (Disposal) Notice 2017 and the requirements of the Resource Management Act for which approval should be sought from the Regional Authority. The substance must be treated and therefore rendered non-hazardous before discharge to the environment.                                               |
| <b>Contaminated packaging</b> | Disposal of contaminated packaging must comply with the Hazardous Substances (Disposal) Notice 2017 clause 12. Ensure that the package is rendered incapable of containing any substance and is disposed in a manner that is consistent with the requirements of the substance it contained and the material of the package. If possible reuse or recycle packaging. |

### 14. Transport Information

#### Land Transport Rule: Dangerous Goods 2005 - NZS 5433:2007

There are no specific restrictions for this product (not a dangerous good).

|                     |    |                      |    |
|---------------------|----|----------------------|----|
| <b>UN number:</b>   | NA | <b>UN number:</b>    | NA |
| <b>Class(es)</b>    | NA | <b>Class(es)</b>     | NA |
| <b>Precautions:</b> | NA | <b>Hazchem code:</b> | NA |
| <b>IMDG</b>         |    |                      |    |
| <b>UN number:</b>   | NA | <b>UN number:</b>    | NA |
| <b>Class(es)</b>    | NA | <b>Class(es)</b>     | NA |
| <b>Precautions:</b> | NA | <b>EMS</b>           | NA |
| <b>IATA</b>         |    |                      |    |
| <b>UN number:</b>   | NA | <b>UN number:</b>    | NA |
| <b>Class(es)</b>    | NA | <b>Class(es)</b>     | NA |
| <b>Precautions:</b> | NA |                      |    |

### 15. Regulatory Information

This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO). Approval code: HSR002545, Construction Products (Carcinogenic) Group Standard 2020. All ingredients appear on the New Zealand Inventory of Chemicals NZIoC.

#### Specific Controls

Key workplace requirements are:

|                                 |                                                                                                                                                                       |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SDS                             | To be available within 10 minutes in workplaces storing any quantity.                                                                                                 |
| Inventory                       | An inventory of all hazardous substances must be prepared and maintained.                                                                                             |
| Packaging                       | All hazardous substances should be appropriately packaged including substances that have been decanted, transferred or manufactured for own use or have been supplied |
| Labelling                       | Must comply with the Hazardous Substances (Labelling) Notice 2017.                                                                                                    |
| Emergency plan                  | Required if > 1000L is stored.                                                                                                                                        |
| Certified handler               | Not required.                                                                                                                                                         |
| Tracking                        | Not required.                                                                                                                                                         |
| Bunding & secondary containment | Not required (non-pooling substance)                                                                                                                                  |
| Signage                         | Required if > 1000L is stored.                                                                                                                                        |
| Location compliance certificate | Not required.                                                                                                                                                         |
| Flammable zone                  | Not required.                                                                                                                                                         |
| Fire extinguisher               | Not required.                                                                                                                                                         |

Note: The above workplace requirements apply if only this particular substance is present. The complete set of controls for a location will depend on the classification and total quantities of other substances present in that location.

#### Other Legislation

In New Zealand, the use of this product may come under the Resource Management Act and Regulations, the Health and Safety at Work Act 2015 and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016, local Council Rules and Regional Council Plans.

#### 16. Other Information

##### Abbreviations

|                        |                                                                                                                                                                                                                                                                                                                                    |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Approval Code</b>   | Approval HSR002545, Construction Products (Carcinogenic) Group Standard 2020 Controls, EPA. <a href="http://www.epa.govt.nz">www.epa.govt.nz</a>                                                                                                                                                                                   |
| <b>CAS Number</b>      | Unique Chemical Abstracts Service Registry Number                                                                                                                                                                                                                                                                                  |
| <b>EC<sub>50</sub></b> | Ecotoxic Concentration 50% – concentration in water which is fatal to 50% of a test population (e.g. daphnia, fish species)                                                                                                                                                                                                        |
| <b>EPA</b>             | Environmental Protection Authority (New Zealand)                                                                                                                                                                                                                                                                                   |
| <b>GHS</b>             | Globally Harmonised System of Classification and Labelling of Chemicals, 7 <sup>th</sup> revised edition, 2017, published by the United Nations.                                                                                                                                                                                   |
| <b>HAZCHEM Code</b>    | Emergency action code of numbers and letters that provide information to emergency services, especially fire fighters                                                                                                                                                                                                              |
| <b>HSNO</b>            | Hazardous Substances and New Organisms (Act and Regulations)                                                                                                                                                                                                                                                                       |
| <b>IARC</b>            | International Agency for Research on Cancer                                                                                                                                                                                                                                                                                        |
| <b>LEL</b>             | Lower Explosive Limit                                                                                                                                                                                                                                                                                                              |
| <b>LD<sub>50</sub></b> | Lethal Dose 50% – dose which is fatal to 50% of a test population (usually rats).                                                                                                                                                                                                                                                  |
| <b>LC<sub>50</sub></b> | Lethal Concentration 50% – concentration in air which is fatal to 50% of a test population (usually rats)                                                                                                                                                                                                                          |
| <b>NZIoC</b>           | New Zealand Inventory of Chemicals                                                                                                                                                                                                                                                                                                 |
| <b>STEL</b>            | Short Term Exposure Limit - The maximum airborne concentration of a chemical or biological agent to which a worker may be exposed in any 15 minute period, provided the TWA is not exceeded                                                                                                                                        |
| <b>STOT RE</b>         | System Target Organ Toxicity – Repeated Exposure                                                                                                                                                                                                                                                                                   |
| <b>TWA</b>             | Time Weighted Average – generally referred to WES averaged over typical work day (usually 8 hours)                                                                                                                                                                                                                                 |
| <b>UEL</b>             | Upper Explosive Limit                                                                                                                                                                                                                                                                                                              |
| <b>UN Number</b>       | United Nations Number                                                                                                                                                                                                                                                                                                              |
| <b>WES</b>             | Workplace Exposure Standard - The airborne concentration of a biological or chemical agent to which a worker may be exposed during work hours (usually 8 hours, 5 days a week). The WES relates to exposure that has been measured by personal monitoring using procedures that gather air samples in the worker's breathing zone. |

##### References

|                          |                                                                                                                                                                                                             |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Data</b>              | Unless otherwise stated comes from the EPA HSNO chemical classification information database (CCID).                                                                                                        |
| <b>Controls</b>          | EPA notices, <a href="http://www.epa.govt.nz">www.epa.govt.nz</a> , Health and Safety at Work (Hazardous Substances) Regulations 2017, <a href="http://www.legislation.govt.nz">www.legislation.govt.nz</a> |
| <b>WES</b>               | The latest NZ Workplace Exposure Standards, published by WorkSafe NZ and available on their web site – <a href="http://www.worksafe.govt.nz">www.worksafe.govt.nz</a> .                                     |
| <b>Other References:</b> | Suppliers SDS                                                                                                                                                                                               |

##### Review

|                      |                          |
|----------------------|--------------------------|
| <b>Date</b>          | Reason for review        |
| <b>February 2026</b> | Not applicable - New SDS |

##### Disclaimer

This SDS was prepared by Datachem LTD and is based on our current state of knowledge, including information obtained from suppliers. The SDS is given in good faith and constitutes a guideline (not a guarantee of safety). The level of risk each substance poses is relevant to its properties (as summarised in the SDS) AND HOW THE SUBSTANCE IS USED. While guidelines are given for personal protective equipment, such precautions must be relevant to the use. The likely GHS 7 classifications for this SDS have been estimated based on general information from the supplier (e.g., hazard, toxicological). This SDS is copyright Datachem and must not be copied, edited or used for other than intended purpose. To contact the SDS author, email [info@datachem.co.nz](mailto:info@datachem.co.nz) or phone: +64 21 1040951.

