# **G LOOK FLOORS**



# STRONGBOND Primer/Sealer

### **Product Features:**

Enhances adhesion Increases spread rate of an adhesive (Saves you money) Prevents bubbling Covers very wide range of substrates: cementitious and wooden floors Reduces substrate porosity User-friendly (can be sprayed, rolled or brushed)

# **Usages and Properties:**

Strongbond Adhesive Primer/Sealer is a water based primer specially formulated to condition a substrate for the further application of a adhesive and display a relatively tough but flexible film. It exhibits excellent adhesion and is recommended for priming any porous and highly absorbent substrates.

It is compatible with all Strongbond Adhesives and improves adhesion.

# Preparation of the Substrate:

The substrate to be primed must be permanently dry (no hydrostatic pressure) and free from weakly bonded components of surfaces. Materials that would impair adhesion, such as oil, grease and paint residues should be removed using suitable methods.

## **Application:**

Strongbond Adhesive Primer/Sealer is applied evenly to a suitably prepared substrate by spraying, rolling or brushing. Do not allow to puddle.

Use Strongbond Adhesive Primer/Sealer for highly porous floors, or floors where a floor levelling compound has been used to improve adhesion on porous substrates such as particle board, plywood and timber substrates, fibre cement board and/or concrete/cements screeds. One coat is sufficient!!!

#### **Technical Data:**

Colour: white (dries clear)

Conditions of use:

Temperature: not below 10°C Relative Humidity: not above 75% Touch dry time: up to 15 minutes

Coverage: 10m<sup>2</sup>/Lt

Storage: store in a cool place. Containers that have been opened must be properly sealed. Storage life: 1-year minimum in the original sealed container

Cleaning Agent: water before drying

Packaging: 15Lt