

Strongbond Plywood Underlayment

FEATURES

- 5.2mm thickness with 1220mm in length and 1220mm in width
- Low formaldehyde E0 emission rating (less than 0.05mg/m3)
- Nominal Density is 615kg/m3
- Moisture 6 to 12%
- 4.81Kg in weight per sheet
- Natural Brown colour

STRONGBOND RAMP EDGE is an underlayment predominantly used for wood sub-floor to provide a smooth and even finish for resilient floor coverings.

PACKAGED 90 sheets loosely stacked on a pallet.

INSTALLATION

For best practice, we would recommend gluing the plywood sheets with Latex Acrylic or PVA based adhesive in a brick pattern. Full trowelled adhesive is required such as STRONGBONG 54P, STRONGBOND 888 or STRONGBOND DIY. The sheet shall be stapled with a 90 series 22mm staples, 50mm around the perimeter of the sheet and 100mm though the centre.

MATERIAL

It is made from three layers of Poplar and finished with Bingtongor face and back.

SUBSTRATE

The substrate must be dry, firm and free from dust. Please ensure the sub-floor ventilation is compliant with New Zealand building code.

Strongbond products are proudly distributed by Look Floors, a division of Flooring Wholesale Limited. Branches Nationwide

www.lookfloors.co.nz

Disclaimer

The technical details, recommendations and other information contained in this product's data sheets are given in good faith and represent the best of our knowledge and experience at the time of printing. It is customer's responsibility to ensure that products are used and handled correctly and in accordance with any applicable local Standard, our instructions and recommendations are only for the uses they are intended. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. The supply of our products and services is subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.

For more information, please check $\underline{www.islimport.com}$

18 January 2024

This data sheet replaces all previous versions.

SAFETY PRECAUTIONS

We would recommend wearing safety PPE gear during installation of this product.

FSC CERTIFICATION

Our ply conforms with the requirements of FSC Chain of Custody Certification standard.

Version 1 Page 1 of 1