



STRONGBOND ROYAL BUILDERS SPEC

TECHNICAL DATA SHEET

APPLICATION AND DESCRIPTION

It is a low density carpet underlay with PE Film adding to the insulation properties of the foam. This product assists the performance of domestic carpet, it makes the floor warmer, quieter and softer.

PRODUCT SPECIFICATIONS

- 8mm thickness with PE Film
- 70kg in density – 1.83m x 15m roll
- 95% is made from recycled cleaned foam material and re-chipped to obtain the density

PRODUCT FEATURES

- Provides additional sound and heat barrier
- Environmentally friendly

COMPOSITION

- Foam content: Re-bonded Polyurethane Foam
- Laminate content: Beige Polyethylene Film (PE)

This product should be laid in accordance with the current Australia/NZ Flooring Standards. For further information, site support and product queries please contact Look Floors

Disclaimer

The information provided is prepared to the best of our current knowledge and makes no claim to be complete. User is responsible for establishing that the product and recommendations herein are fit for the designated purpose before use. Look Floors can only guarantee the delivered product. A professional and thereby successful application of the product is beyond our control. If in doubt, make a preliminary test. User is required to read and understand all information contained on package labels and safety data sheets before using this product.

10 September 2020
This data sheet replaces all previous versions

