



STRONGBOND TIMBER UNDERLAY

TECHNICAL DATA SHEET

APPLICATION AND DESCRIPTION

It is a high density underlay with aluminium gold foil and integrated backing fleece that acts as an additional sound and moisture barrier adding to the insulation properties of your environment. It is used for engineered wood and laminate flooring. This product assists the performance of timber flooring products, it makes the floor warmer, quieter and softer.

PRODUCT SPECIFICATIONS

- 3mm thickness
- 10m² roll (10m length x 1m height)
- 95% is made from recycled foam waste material
- 23db sound insulation
- 1.01 TOG heat insulation

PRODUCT FEATURES

- Provides additional moisture protection
- Provides additional sound barrier
- Environmentally friendly
- Suits low temperature underfloor heating systems with temperature less than 45°C

COMPOSITION

INFORMATION ON MATERIAL			
CHEMICAL NAME	PERCENT BY WEIGHT	CAS No.	EC#
Polyurethane Foam	95%	9009-54-5	Unlisted
BOPP	4.5%	9003-07-0	Unlisted
Aluminium (AL)	0.1%	7429-90-5	231-072-3
Ethylene-vinyl Acetate Copolymer	0.4%	24937-78-8	Unlisted

This product should be laid in accordance with the current Australia/NZ Flooring Standards. For further information, site support and product queries please contact Look Floors

Disclaimer: The information provided is prepared to the best of our current knowledge and makes no claim to be complete. User is responsible for establishing that the product and recommendations herein are fit for the designated purpose before use. Look Floors can only guarantee the delivered product. A professional and thereby successful application of the product is beyond our control. If in doubt, make a preliminary test. User is required to read and understand all information contained on package labels and safety data sheets before using this product.

10 September 2020
This data sheet replaces all previous versions