



FLOORING WHOLESALE LIMITED

9 Industry Road, Penrose, 1642,
Auckland, New Zealand

+64 9 525 0652

info@lookfloors.co.nz

Lookfloors.co.nz

Description

Strongbond Stairnosings are prefinished extruded aluminium profiles for fixing to the edge of stair treads.

Intended Use

Strongbond Stair Nosings are installed at the edge of stairs treads to enhance visibility of the edge of the tread and to prevent slips.

Technical Literature

- Contact Look Floors for further technical information if required.

Building Code Compliance

When used as described in this PTS, Strongbond Stair Nosings meet or contribute to the following relevant performance requirements of the New Zealand Building Code

Clause B2 Durability: Performance Clauses B2.3.1(c)

Clause D1 Access routes: Performance Clauses D1.3.1.3(d, g)

Clause F2 Hazardous building materials: Performance Clauses F2.3.1

Clause B2 Durability: Performance Clauses B2.3.1(c)

Basis Verification method B2/VM1

Strongbond Stair Nosings are manufactured from aluminium. They are durable and are readily accessed should they need replacement.

Clause D1 Access routes: Performance Clauses D1.3.1.3(d, g)

Basis Acceptable Solution D1/AS1

Strongbond Stair Nosings are 50 mm wide, rounded and available in colours to provide contrast with the rest of the stair tread.

Clause F2 Hazardous building materials: Performance Clauses F2.3.1

Basis By testing and comparison with the performance requirements of New Zealand Building Code clause F2.3.1

Strongbond Stair Nosings do not give rise to harmful concentrations of gas, liquid, radiation or solid particles at the surface of the material where the material is exposed, or in the atmosphere of any space.

Supporting Information

- Acceptable Solutions and Verification Methods for New Zealand Building Code Clause B2 Durability Second edition (Amendment 12), 28 November 2019
- Acceptable Solutions and Verification Methods for New Zealand Building Code Clause D1 Access Routes Second edition (Amendment 6), 1 January 2017

Conditions

Strongbond Stairnosings are suitable for use in access routes in all buildings.

Supplementary Information

Unique product codes/IDs:

- Strongbond Commercial Stairnosing 3M: 21272 (Silver), 21273 (Pewter), 21274 (LF Champagne)
- Strongbond Bullnose Commercial Stairnosing 3M: 21795 (Silver), 21796 (LF Champagne) , 21797 (Pewter)

This product is not subject to any warning or ban declared by MBIE under section 26 of the Building Act 2004.

This product is manufactured by ISL Danyany Co.,LTD, trading as ISL Danyany Co.,LTD, YUNYANG HIGH-TECH ZONE, DANYANG 212300, JIANGSU,CHINA , sales@islimport.com, www.islimport.com and imported by FLOORING WHOLESALE LIMITED, NZBN 9429037924218 trading as Look Floors, 9 Industry Road, Penrose, 1642, Auckland, New Zealand , info@lookfloors.co.nz, Lookfloors.co.nz
