



Bona DriFast® Stain

Oil-Modified Stain for Interior Hardwood Floors.

Provides speed and high performance for hardwood floor finishing



Bona DriFast® Stain is a premium quality quick-drying stain for interior hardwood floors, DriFast Stain's advanced technology formula provides speed and high performance for hardwood floor finishing professionals. Compatible with all Bona® waterborne systems and all other Bona® Finish Systems.

- 2-hour dry time*
- No bleed back
- Penetrates, stains, and seals bare wood
- 800-1,000 sq. ft/gal coverage rate
- Available in 25 wood tones and white
- All stain colors can be blended, offering an endless color palette
- Clean up with mineral spirits
- Easy touch-ups

*6 hours minimum for white and 12-18 hours for Ebony, Spice Brown, Bark and Cocoa under ideal conditions of 60°-80° F(16°-27°C) with 35-75% relative humidity



Bona DriFast® Stain

Oil-Modified Stain for Interior Hardwood Floors.

Provides speed and high performance for hardwood floor finishing

PHYSICAL CHARACTERISTICS

Ingredients – *Wood tones*: Oil-modified resins, mineral spirits (solvent), pigments, driers

White: Oil-modified resins, mineral spirits (solvent), titanium dioxide, fillers

Colors – *Wood tones*: Natural, Golden Oak, Nutmeg, Early American, Provincial, Special Walnut, Rosewood, Red Mahogany, Jacobean, Graphite, Medium Brown, Antique Brown, Puritan Pine, Cherry, Sedona Red, Spice Brown, Grey, Ebony, Bark, Cocoa, Driftwood, Birch, Aged Pewter, Twig and Sand Dune.

Solids – 35-47%

Density – *Wood tones*: 7.2-7.5 lbs./gallon (0.86-0.90 sg), *White*: 8.7-9.0 lbs./gallon (1.04-1.8 sg)

US Regulatory VOC – 550 g/L

Odor – Mild solvent odor

Stability – Two-year shelf life in unopened container

Flashpoint – 116.6°F (47°C)

Packaging – 1-quart cans, 1-gallon cans

APPLICATION CHARACTERISTICS

Clarity – Semi-transparent (dry)

Drying Time – 2 hours for wood tones, 6 hours minimum for white and 12-18 hours for Ebony, Spice Brown, Bark and Cocoa under ideal conditions of 60°-80° F (16°-27°C) with 35-75% relative humidity.

Coverage – 800-1,000 square feet per gallon

Application Tools – Clean cloths, brush, cut-in pad

RECOMMENDED USE

Prepares the surface for a topcoat of Bona® waterborne or any other Bona® finish. Apply only over bare wood

BEFORE USING, READ ALL DIRECTIONS AND SAFETY DATA SHEETS.

FOR TECHNICAL ADVICE: Call Bona US at 800-872-5515

RESPONSE

Get medical attention if you feel unwell. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. If skin irritation occurs: Get medical attention.

COMPATIBILITY

Stain, sealer, and finish results may vary widely depending on the wood species, especially on oily and resinous exotics. ALWAYS PREPARE A SAMPLE OR TEST AREA TO DETERMINE COMPATIBILITY, APPEARANCE AND DESIRED RESULTS.

SANDING AND PREPARATION OF NEW FLOORS

1. Sand and prepare floor using accepted industry association methods. 2. Make your final cut with 80 to 100-grit paper and MultiDisc with an 80 to 120-grit. 3. Use a Tampico Brush on a buffer and vacuum thoroughly. 4. Tack with a dry Bona® Microfiber Mop or cloth to remove dust. 5. Apply stain system.

THE BONA DriFast® STAIN SYSTEM

Bona DriFast Stain is a redissolving stain designed to penetrate, stain and seal bare wood. Bona DriFast Stain is designed to work with all Bona finishes. Colors may be blended with all other Bona DriFast Stains. Visit www.bona.com for additional product information

RECOMMENDED APPLICATORS

Brush, cut-in pad, cloth, carpet disc



Bona DriFast® Stain

Oil-Modified Stain for Interior Hardwood Floors.

Provides speed and high performance for hardwood floor finishing

MIXING INSTRUCTIONS

SHAKE AND STIR WELL BEFORE USING. DO NOT THIN.

STAINING

1. After preparing surface, apply Bona DriFast Stain with brush, cut-in pad, cloth, or carpet disc driven by a buffer in the direction of the grain at the coverage rate of 800 – 1000 square feet per gallon. 2. Allow 1-3 minutes for penetration. Remove excess by hand wiping or buffing with an absorbent, non-abrasive material. 3. Allow stain to dry thoroughly (minimum 2 hours for wood tones, 6 hours minimum for white and 12-18 hours for Ebony, Spice Brown, Bark and Cocoa under ideal conditions of 60°-80° F(16°-27°C) with 35-75% relative humidity. High humidity and/or low temperature conditions will extend dry time, while increased ventilation and airflow will reduce dry time. Apply sealer or finish after the recommended dry time, but within 48 hours after application. 4. Apply any Bona finish system over thoroughly dried stain.

ORDER INFORMATION

Item #	Description	Size	#/Case	Weight lbs.
SS750051100	Natural	Quart	6	12.5
SS750051101	Nutmeg	Quart	6	12.5
SS750051102	Golden Oak	Quart	6	12.5
SS750051103	Early American	Quart	6	12.5
SS750051104	Provincial	Quart	6	12.5
SS750051105	Special Walnut	Quart	6	12.5
SS750051106	Rosewood	Quart	6	12.5
SS750051107	Red Mahogany	Quart	6	12.5
SS750051108	Jacobean	Quart	6	12.5
SS750051109	Graphite	Quart	6	12.5

CLEAN-UP

Clean applicator tools and equipment with mineral spirits.

STABILITY

Two year shelf life in unopened container

STORAGE AND DISPOSAL

Store at room temperature. Keep container closed when not in use. Do not store above 100°F (38°C). Do not transfer contents to other containers for storage and disposal. In case of spillage, absorb with inert material. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

DANGER

RAGS, STEEL WOOL OR WASTE SOAKED WITH BONA DRIFAST STAIN MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED, WATER-FILLED, METAL CONTAINER.



Bona DriFast® Stain

Oil-Modified Stain for Interior Hardwood Floors.

Provides speed and high performance for hardwood floor finishing

SS750051110	White	Quart	6	12.5
SS750051111	Medium Brown	Quart	6	12.5
SS750051112	Antique Brown	Quart	6	12.5
SS750051113	Puritan Pine	Quart	6	12.5
SS750051114	Cherry	Quart	6	12.5
SS750051174	Spice Brown	Quart	6	12.5
SS750051175	Sedona Red	Quart	6	12.5
SS750051176	Grey	Quart	6	12.5
SS750051177	Ebony	Quart	6	12.5
SS750051178	Bark	Quart	6	12.5
SS750051179	Cocoa	Quart	6	12.5
SS750051180	Driftwood	Quart	6	12.5
SS750051181	Birch	Quart	6	12.5
SS750051182	Aged Pewter	Quart	6	12.5
SS750051183	Twig	Quart	6	12.5
SS750051184	Sand Dune	Quart	6	33.13
SS750018100	Natural	Gallon	4	33.13
SS750018101	Nutmeg	Gallon	4	33.13
SS750018102	Golden Oak	Gallon	4	33.13
SS750018103	Early American	Gallon	4	33.13
SS750018104	Provincial	Gallon	4	33.13
SS750018105	Special Walnut	Gallon	4	33.13
SS750018106	Rosewood	Gallon	4	33.13
SS750018107	Red Mahogany	Gallon	4	33.13
SS750018108	Jacobean	Gallon	4	33.13
SS750018109	Graphite	Gallon	4	33.13
SS750018110	White	Gallon	4	33.13
SS750018111	Medium Brown	Gallon	4	33.13
SS750018112	Antique Brown	Gallon	4	33.13
SS750018113	Puritan Pine	Gallon	4	33.13
SS750018114	Cherry	Gallon	4	33.13
SS750018160	Ebony	Gallon	4	33.13



Bona DriFast® Stain

Oil-Modified Stain for Interior Hardwood Floors.

Provides speed and high performance for hardwood floor finishing

SS750018161	Grey	Gallon	4	33.13
SSS750018166	Spice Brown	Gallon	4	33.13
SS750018165	Sedona Red	Gallon	4	33.13
SS750018167	Bark	Gallon	4	33.13
SS750018168	Cocoa	Gallon	4	33.13
SS750018169	Driftwood	Gallon	4	33.13
SS750018170	Birch	Gallon	4	33.13
SS750018171	Aged Pewter	Gallon	4	33.13
SS750018172	Twig	Gallon	4	33.13
SS750018173	Sand Dune	Gallon	4	33.13