

BONA
CRAFT OIL 2K



Create **your** own wood **story**

BONA OIL SYSTEM – UNIQUE CHARACTERS ON WOODEN FLOORS



Natural solutions for healthy floors

Bona's complete range of oils are renewable, made using raw vegetable materials and contain exceptionally low levels of VOC and contains no hazardous agents such as cobalt and ketoximes. Their high oil content ensures a high degree of saturation with fewer applications for healthy floors and long-lasting protection.

- ✓ Natural solutions
- ✓ Child safe
- ✓ Cobalt free

Bona Craft Oil 2K

Releasing Oil Potential

Performance, versatility and design – get the charming look and feel of an oiled wood floor, plus the protection of a finish. The unique formula delivers a beautiful, strong surface that is resistant to water and stains. It can be used on its own as a quick drying, high-performance oil, or combined with a lacquer, for desired gloss effect and a practically maintenance-free wood surface.

COLOUR VERSIONS



APPLICATION

Bona Craft Oil 2K is suitable for wooden floors in residential or medium wear commercial environments, as well as for furniture and other woodwork. It works perfectly with a wide variety of wood species, including otherwise problematic ones, such as cherry, walnut, smoked oak and steamed beech.

KEY BENEFITS

- Extremely high degree of saturation
- Fast drying, with long open time and pot life
- Quick and easy to apply
- Uniform colouration
- Easy repair and blending
- Good resistance to water and chemicals
- Very low solvent content
- Overcoatable with Traffic, Traffic HD and Traffic Natural
- Complies with EN 71-3 for application on children's toys

TECHNICAL DATA

Product base:	Modified vegetable oils + isocyanate hardener
VOC:	Max 19g/litre (incl. hardener)
Mixing ratio:	9 parts oil (Component A) to 1 part hardener (Component B), 10%
Pot Life:	6-8 hours
Drying time:	Between applications: 15-30 minutes* Light use: Neutral/8 hours* Coloured/12 hours* *under normal indoor conditions, 23°C/50% R.H. ensure proper ventilation.
Application tools:	Bona Oil Squeegee, short-haired roller or stainless steel trowel
Total consumption:	Approx. 30 m ² /litre depending on wood type
Cleaning:	Use clean tools with white spirit and dried material can be removed with white spirit
Shelf life:	2 years, from the date of production, in unopened original container
Storage/transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport
Sizes:	6 x 1.25 litre (1125 ml oil + 125 ml hardener)